



Rocky Enterprise Linux 9.2 Manual Pages on command 'flatpak-repair.1'

\$ man flatpak-repair.1

FLATPAK REPAIR(1) flatpak repair FLATPAK REPAIR(1)

NAME

flatpak-repair - Repair a flatpak installation

SYNOPSIS

flatpak repair [OPTION...]

DESCRIPTION

Repair a flatpak installation by pruning and reinstalling invalid objects. The repair command does all of the following:

- ? Scan all locally available refs, removing any that don't correspond to a deployed ref.
- ? Verify each commit they point to, removing any invalid objects and noting any missing objects.
- ? Remove any refs that had an invalid object, and any non-partial refs that had missing objects.
- ? Prune all objects not referenced by a ref, which gets rid of any possibly invalid non-scanned objects.
- ? Enumerate all deployed refs and re-install any that are not in the repo (or are partial for a non-subdir deploy).

Note that flatpak repair has to be run with root privileges to operate on the system installation.

An alternative command for repairing OSTree repositories is `ostree fsck`.

OPTIONS

The following options are understood:

`-h, --help`

Show help options and exit.

`--user`

Repair per-user installation.

`--system`

Repair system-wide installation.

`--installation=NAME`

Repair the system-wide installation specified by NAME among those defined in `/etc/flatpak/installations.d/`. Using

`--installation=default` is equivalent to using `--system`.

`--dry-run`

Only report inconsistencies, don't make any changes

`--reinstall-all`

Reinstall all refs, regardless of whether they were removed from the repo or not

`-v, --verbose`

Print debug information during command processing.

`--ostree-verbose`

Print OSTree debug information during command processing.

EXAMPLES

```
$ sudo flatpak repair
```

```
$ flatpak repair --user
```

SEE ALSO

`flatpak(1)`, `ostree-fsck(1)`

flatpak

FLATPAK REPAIR(1)