



Rocky Enterprise Linux 9.2 Manual Pages on command 'foomatic-addpjloptions.8'

\$ man foomatic-addpjloptions.8

FOOMATIC-ADDPJLOPTIONS(8) System Manager's Manual FOOOMATIC-ADDPJLOPTIONS(8)

NAME

foomatic-addpjloptions - Format PjL option information the for foomatic database

SYNOPSIS

```
foomatic-addpjloptions [-dafis][-o dir] -p printer_ID [pjl_info_file]
foomatic-addpjloptions [-dafq] [pjl_info_file]
foomatic-addpjloptions -h
```

Description

foomatic-addpjloptions formats the PjL information file (or STDIN) into a format usable by the Foomatic database.

Options

- a Convert all PjL options in the information file.
- d Enable debugging information.
- f Do not ask for permission, force conversion.
- h Print a help message and exit.
- q Print a summary of the PjL information. This output is not compatible with the foomatic database, and is useful for debugging.

-s Produce a single option file containing all the option values.

-o dir

The directory the option information files are written to.

-p printer_ID

Name of the printer in the foomatic database. This is used to ex?

tract printer manufacturer and model information.

pjl_info_file

File with PJP information returned by the printer. If this file?

name is not provided, the PJP options are taken from standard in?

put.

FILES

/usr/share/foomatic/templates/pjl*.xml

Template files for option information.

./foomatic-db/opts

Option information stored in this directory.

EXIT STATUS

foomatic-addpjloptions returns 0 on success, and a nonzero value on

failure.

AUTHOR

Manfred Wassmann <manolo@NCC-1701.B.Shuttle.de> for the foomatic project using output from the associated binary.

Modified by Patrick Powell (<papowell at astart.com>).

BUGS

Please post bug reports on

<http://lists.freestandards.org/mailman/listinfo/printing-foomatic>

Foomatic Project 2001-05-07 FOOMATIC-ADDPJLOPTIONS(8)