



Rocky Enterprise Linux 9.2 Manual Pages on command 'foomatic-compiledb.1'

\$ man foomatic-compiledb.1

FOOMATIC-COMPILEDDB(1) General Commands Manual FOOMATIC-COMPILEDDB(1)

NAME

foomatic-compiledb - Compile the Foomatic printer/driver database

SYNOPSIS

foomatic-compiledb [-t type] [-f] [-j n] [driver ...]

DESCRIPTION

foomatic-compiledb generates all PPD files or Foomatic combo XML files for all possible printer/driver combos, or only for a selected range of drivers. It generally should not be necessary except for people who want to generate a set of Foomatic data files for distribution. For configuring single printers foomatic-ppdfile(1) and especially foomatic-configure(1) will automatically compute just what they need.

Options

- t type Output file type, either ppd or xml.
- f Force: Write into the destination directory even if it already exists.
- j n n = number of work processes to run
- driver ...

only generate data files for these driver(s)

SEE ALSO

foomatic-ppdf(1),foomatic-configure(1)

EXIT STATUS

foomatic-compiledb returns 0 unless something unexpected happens.

AUTHORS

Manfred Wassmann <manolo@NCC-1701.B.Shuttle.de> and Till Kamppeter
<till.kamppeter@gmail.com> for the foomatic project using output from
the associated binary.

BUGS

Existing files are always conserved instead of older files being over?
written. So deleting the destination directory (rm -rf dir) and calling
foomatic-compiledb without the -f option is recommended.

Please post bug reports on

<http://lists.freestandards.org/mailman/listinfo/printing-foomatic>

Foomatic Project 2001-05-07 FOOMATIC-COMPILEDDB(1)