



### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'fprintd.1'***

#### ***\$ man fprintd.1***

fprintd(1) fprintd(1)

#### NAME

fprintd - Fingerprint management daemon, and test applications

#### SYNOPSIS

fprintd-enroll [-f finger] [username]

fprintd-list username [usernames...]

fprintd-verify [-f finger] [username]

fprintd-delete username [usernames...]

#### DESCRIPTION

This manual page documents briefly the fprintd command-line utilities.

The fprintd daemon is accessed through D-Bus by those command-line utilities.

#### ARGUMENTS

username

The username for the user for which you want to query or modify the fingerprint database.

Not that fprintd-list and fprintd-delete require at least one username to be passed, and support multiple usernames.

fprintd-enroll and fprintd-verify will use the current username if none are passed on the command-line.

#### -f finger

For fprintd-enroll, the finger to enroll. Possible values are:

left-thumb, left-index-finger, left-middle-finger, left-ring-finger, left-little-finger, right-thumb, right-index-finger, right-middle-finger, right-ring-finger, right-little-finger.

The default is automatic, selecting the first available finger for swipe devices, or all the enrolled fingers, for press devices.

## TEST APPLICATIONS

### fprintd-enroll

Will enroll the user's right index finger into the database.

### fprintd-list

Will list the user's enrolled fingerprints.

### fprintd-verify

Will verify the user's fingerprints against the database.

### fprintd-enroll

Will enroll the user's right index finger into the database.

## AUTHOR

fprintd was written by Bastien Nocera and Daniel Drake.

## DIRECTORIES

By default, fprintd stores the fingerprints in /var/lib/fprint/

## SEE ALSO

gnome-control-center

freedesktop

2021-08-26

fprintd(1)