



Rocky Enterprise Linux 9.2 Manual Pages on command 'grub2-reboot.8'

\$ man grub2-reboot.8

GRUB-REBOOT(8) System Administration Utilities GRUB-REBOOT(8)

NAME

grub-reboot - set the default boot entry for GRUB, for the next boot only

SYNOPSIS

grub-reboot [OPTION] MENU_ENTRY

DESCRIPTION

Set the default boot menu entry for GRUB, for the next boot only.

-h, --help

print this message and exit

-V, --version

print the version information and exit

--boot-directory=DIR

expect GRUB images under the directory DIR/grub2 instead of the /boot/grub2 directory

MENU_ENTRY is a number, a menu item title or a menu item identifier.

Please note that menu items in submenus or sub-submenus require specifying

the submenu components and then the menu item component. The title

files should be separated using the greater-than character (>) with no extra spaces. Depending on your shell some characters including > may need escaping. More information about this is available in the GRUB Manual in the section about the 'default' command.

NOTE: In cases where GRUB cannot write to the environment block, such as when it is stored on an MDRAID or LVM device, the chosen boot menu entry will remain the default even after reboot.

REPORTING BUGS

Report bugs to <bug-grub@gnu.org>.

SEE ALSO

grub-set-default(8), grub-editenv(1)

The full documentation for grub-reboot is maintained as a Texinfo manual. If the info and grub-reboot programs are properly installed at your site, the command

info grub-reboot

should give you access to the complete manual.