



Rocky Enterprise Linux 9.2 Manual Pages on command 'iscsid.8'

\$ man iscsid.8

ISCSID(8) Linux Administrator's Manual ISCSID(8)

NAME

iscsid - Open-iSCSI daemon

SYNOPSIS

iscsid [OPTION]

DESCRIPTION

The iscsid implements the control path of iSCSI protocol, plus some management facilities. For example, the daemon could be configured to automatically re-start discovery at startup, based on the contents of persistent iSCSI database.

OPTIONS

[-c|--config=]config-file

Read configuration from config-file rather than the default
/etc/iscsi/iscsid.conf file.

[-i|--initiatorname=]iname-file

Read initiator name from iname-file rather than the default
/etc/iscsi/initiatorname.iscsi file.

[-f|--foreground]

run iscsid in the foreground. Implies --no-pid-file.

`[-d|--debug=]debug_level`

print debugging information. Valid values for debug_level are 0 to 8.

`[-u|--uid=]uid`

run under user ID uid (default is the current user ID).

`[-g|--gid=]gid`

run under user group ID gid (default is the current user group ID).

`[-n|--no-pid-file]`

do not write a process ID file. Conflicts with the --pid= option.

`[-p|--pid=]pid-file`

write process ID to pid-file rather than the default /run/iscsid.pid. Conflicts with the --no-pid-file option.

`[-h|--help]`

display this help and exit

`[-v|--version]`

display version and exit.

FILES

`/etc/iscsi/iscsid.conf`

The configuration file read by iscsid and iscsiadm on startup.

`/etc/iscsi/initiatorname.iscsi`

The file containing the iSCSI initiatorname and initiatoralias read by iscsid and iscsiadm on startup.

`/var/lib/iscsi/nodes`

Open-iSCSI persistent configuration database

SEE ALSO

iscsiadm(8)

AUTHORS

Open-iSCSI project <<http://www.open-iscsi.com/>>

Alex Aizman <itn780@yahoo.com>

Dmitry Yusupov <dmitry_yus@yahoo.com>

