



Rocky Enterprise Linux 9.2 Manual Pages on command 'iswspace.3'

\$ man iswspace.3

ISWSPACE(3) Linux Programmer's Manual ISWSPACE(3)

NAME

iswspace - test for whitespace wide character

SYNOPSIS

```
#include <wctype.h>

int iswspace(wint_t wc);
```

DESCRIPTION

The `iswspace()` function is the wide-character equivalent of the `isspace(3)` function. It tests whether `wc` is a wide character belonging to the wide-character class "space".

The wide-character class "space" is disjoint from the wide-character class "graph" and therefore also disjoint from its subclasses "alnum", "alpha", "upper", "lower", "digit", "xdigit", "punct".

The wide-character class "space" contains the wide-character class "blank".

The wide-character class "space" always contains at least the space character and the control characters '\f', '\n', '\r', '\t', '\v'.

RETURN VALUE

The `iswspace()` function returns nonzero if `wc` is a wide character belonging to the wide-character class "space". Otherwise, it returns zero.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?iswspace() ? Thread safety ? MT-Safe locale ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

NOTES

The behavior of `iswspace()` depends on the `LC_CTYPE` category of the current locale.

SEE ALSO

`isspace(3)`, `iswctype(3)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU 2019-03-06 ISWSPACE(3)