



Rocky Enterprise Linux 9.2 Manual Pages on command 'jnf.3'

\$ man jnf.3

J0(3) Linux Programmer's Manual J0(3)

NAME

j0, j0f, j0l, j1, j1f, j1l, jn, jnf, jnl - Bessel functions of the
first kind

SYNOPSIS

```
#include <math.h>

double j0(double x);
double j1(double x);
double jn(int n, double x);
float j0f(float x);
float j1f(float x);
float jnf(int n, float x);
long double j0l(long double x);
long double j1l(long double x);
long double jnl(int n, long double x);

Link with -lm.
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

j0(), j1(), jn():

`_XOPEN_SOURCE`

`|| /* Since glibc 2.19: */ _DEFAULT_SOURCE`

`|| /* Glibc versions <= 2.19: */ _SVID_SOURCE || _BSD_SOURCE`

`j0f(), j0l(), j1f(), j1l(), jnf(), jnl():`

`_XOPEN_SOURCE >= 600`

`|| (_ISOC99_SOURCE && _XOPEN_SOURCE)`

`|| /* Since glibc 2.19: */ _DEFAULT_SOURCE`

`|| /* Glibc versions <= 2.19: */ _SVID_SOURCE || _BSD_SOURCE`

DESCRIPTION

The `j0()` and `j1()` functions return Bessel functions of x of the first kind of orders 0 and 1, respectively. The `jn()` function returns the Bessel function of x of the first kind of order n .

The `j0f()`, `j1f()`, and `jnf()` functions are versions that take and return float values. The `j0l()`, `j1l()`, and `jnl()` functions are versions that take and return long double values.

RETURN VALUE

On success, these functions return the appropriate Bessel value of the first kind for x .

If x is a NaN, a NaN is returned.

If x is too large in magnitude, or the result underflows, a range error occurs, and the return value is 0.

ERRORS

See `math_error(7)` for information on how to determine whether an error has occurred when calling these functions.

The following errors can occur:

Range error: result underflow, or x is too large in magnitude

`errno` is set to `ERANGE`.

These functions do not raise exceptions for `fetestexcept(3)`.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

?Interface ? Attribute ? Value ?

??

?j0(), j0f(), j0l() ? Thread safety ? MT-Safe ?

??

?j1(), j1f(), j1l() ? Thread safety ? MT-Safe ?

??

?jn(), jnf(), jnl() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

The functions returning double conform to SVr4, 4.3BSD, POSIX.1-2001, and POSIX.1-2008. The others are nonstandard functions that also exist on the BSDs.

BUGS

There are errors of up to 2e-16 in the values returned by j0(), j1(), and jn() for values of x between -8 and 8.

SEE ALSO

y0(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2020-12-21

J0(3)