

Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'loop.4'

\$ man loop.4

LOOP(4)

Linux Programmer's Manual

LOOP(4)

NAME

loop, loop-control - loop devices

SYNOPSIS

#include linux/loop.h>

DESCRIPTION

The loop device is a block device that maps its data blocks not to a physical device such as a hard disk or optical disk drive, but to the blocks of a regular file in a filesystem or to another block device.

This can be useful for example to provide a block device for a filesys? tem image stored in a file, so that it can be mounted with the mount(8) command. You could do

\$ dd if=/dev/zero of=file.img bs=1MiB count=10

\$ sudo losetup /dev/loop4 file.img

\$ sudo mkfs -t ext4 /dev/loop4

\$ sudo mkdir /myloopdev

\$ sudo mount /dev/loop4 /myloopdev

See losetup(8) for another example.

A transfer function can be specified for each loop device for encryp? tion and decryption purposes. The following ioctl(2) operations are provided by the loop block de? vice: LOOP_SET_FD Associate the loop device with the open file whose file descrip? tor is passed as the (third) ioctl(2) argument. LOOP_CLR_FD Disassociate the loop device from any file descriptor. LOOP_SET_STATUS Set the status of the loop device using the (third) ioctl(2) ar? gument. This argument is a pointer to a loop_info structure, defined in linux/loop.h> as: struct loop_info { int lo_number; /* ioctl r/o */ /* ioctl r/o */ dev_t lo_device; /* ioctl r/o */ unsigned long lo_inode; lo rdevice; /* ioctl r/o */ dev t lo_offset; int int lo_encrypt_type; lo_encrypt_key_size; /* ioctl w/o */ int lo_flags; int /* ioctl r/w (r/o before Linux 2.6.25) */ char lo_name[LO_NAME_SIZE]; unsigned char lo_encrypt_key[LO_KEY_SIZE]; /* ioctl w/o */ unsigned long lo_init[2]; char reserved[4]; }; The encryption type (lo_encrypt_type) should be one of LO_CRYPT_NONE, LO_CRYPT_XOR, LO_CRYPT_DES, LO_CRYPT_FISH2, LO_CRYPT_BLOW, LO_CRYPT_CAST128, LO_CRYPT_IDEA, LO_CRYPT_DUMMY,

LO_CRYPT_SKIPJACK, or (since Linux 2.6.0) LO_CRYPT_CRYPTOAPI.

The lo_flags field is a bit mask that can include zero or more of the following:

LO_FLAGS_READ_ONLY

The loopback device is read-only.

LO_FLAGS_AUTOCLEAR (since Linux 2.6.25)

The loopback device will autodestruct on last close.

LO_FLAGS_PARTSCAN (since Linux 3.2)

Allow automatic partition scanning.

LO FLAGS DIRECT IO (since Linux 4.10)

Use direct I/O mode to access the backing file.

The only lo_flags that can be modified by LOOP_SET_STATUS are LO_FLAGS_AUTOCLEAR and LO_FLAGS_PARTSCAN.

LOOP_GET_STATUS

Get the status of the loop device. The (third) ioctl(2) argu? ment must be a pointer to a struct loop_info.

LOOP_CHANGE_FD (since Linux 2.6.5)

Switch the backing store of the loop device to the new file identified file descriptor specified in the (third) ioctl(2) ar? gument, which is an integer. This operation is possible only if the loop device is read-only and the new backing store is the same size and type as the old backing store.

LOOP_SET_CAPACITY (since Linux 2.6.30)

Resize a live loop device. One can change the size of the un? derlying backing store and then use this operation so that the loop driver learns about the new size. This operation takes no argument.

LOOP_SET_DIRECT_IO (since Linux 4.10)

Set DIRECT I/O mode on the loop device, so that it can be used to open backing file. The (third) ioctl(2) argument is an un? signed long value. A nonzero represents direct I/O mode.

LOOP_SET_BLOCK_SIZE (since Linux 4.14)

Set the block size of the loop device. The (third) ioctl(2) ar? gument is an unsigned long value. This value must be a power of

```
two in the range [512,pagesize]; otherwise, an EINVAL error re?
    sults.
LOOP_CONFIGURE (since Linux 5.8)
    Setup and configure all loop device parameters in a single step
    using the (third) ioctl(2) argument. This argument is a pointer
    to a loop_config structure, defined in linux/loop.h> as:
      struct loop_config {
         __u32
                        fd;
         u32
                        block size;
         struct loop info64 info;
         __u64
                       __reserved[8];
      };
    In addition to doing what LOOP_SET_STATUS can do, LOOP_CONFIGURE
    can also be used to do the following:
    * set the correct block size immediately by setting loop_con?
     fig.block_size;
    * explicitly request direct I/O mode by setting LO_FLAGS_DI?
     RECT IO in loop config.info.lo flags; and
    * explicitly request read-only mode by
                                                   setting
     LO_FLAGS_READ_ONLY in loop_config.info.lo_flags.
Since Linux 2.6, there are two new ioctl(2) operations:
LOOP_SET_STATUS64, LOOP_GET_STATUS64
    These are similar to LOOP_SET_STATUS and LOOP_GET_STATUS de?
    scribed above but use the loop_info64 structure, which has some
    additional fields and a larger range for some other fields:
      struct loop info64 {
         uint64_t lo_device; /* ioctl r/o */
         uint64_t lo_inode;
                                /* ioctl r/o */
         uint64_t lo_rdevice;
                                /* ioctl r/o */
         uint64 t lo offset;
         uint64_t lo_sizelimit; /* bytes, 0 == max available */
         uint32_t lo_number;
                                  /* ioctl r/o */
```

uint32_t lo_encrypt_type;

```
uint32_t lo_encrypt_key_size; /* ioctl w/o */
uint32_t lo_flags; i /* ioctl r/w (r/o before

Linux 2.6.25) */
uint8_t lo_file_name[LO_NAME_SIZE];
uint8_t lo_crypt_name[LO_NAME_SIZE];
uint8_t lo_encrypt_key[LO_KEY_SIZE]; /* ioctl w/o */
uint64_t lo_init[2];
};
```

/dev/loop-control

Since Linux 3.1, the kernel provides the /dev/loop-control device, which permits an application to dynamically find a free device, and to add and remove loop devices from the system. To perform these opera? tions, one first opens /dev/loop-control and then employs one of the following ioctl(2) operations:

LOOP_CTL_GET_FREE

Allocate or find a free loop device for use. On success, the device number is returned as the result of the call. This oper? ation takes no argument.

LOOP CTL ADD

Add the new loop device whose device number is specified as a long integer in the third ioctl(2) argument. On success, the device index is returned as the result of the call. If the de? vice is already allocated, the call fails with the error EEXIST.

LOOP_CTL_REMOVE

Remove the loop device whose device number is specified as a long integer in the third ioctl(2) argument. On success, the device number is returned as the result of the call. If the de? vice is in use, the call fails with the error EBUSY.

FILES

/dev/loop*

The loop block special device files.

EXAMPLES

```
device, opens the loop device, opens a file to be used as the underly?
  ing storage for the device, and then associates the loop device with
  the backing store. The following shell session demonstrates the use of
  the program:
    $ dd if=/dev/zero of=file.img bs=1MiB count=10
    10+0 records in
    10+0 records out
    10485760 bytes (10 MB) copied, 0.00609385 s, 1.7 GB/s
    $ sudo ./mnt loop file.img
    loopname = /dev/loop5
Program source
  #include <fcntl.h>
  #include linux/loop.h>
  #include <sys/ioctl.h>
  #include <stdio.h>
  #include <stdlib.h>
  #include <unistd.h>
  #define errExit(msg) do { perror(msg); exit(EXIT_FAILURE); \
                 } while (0)
  int
  main(int argc, char *argv[])
  {
    int loopctlfd, loopfd, backingfile;
    long devnr;
    char loopname[4096];
    if (argc != 2) {
       fprintf(stderr, "Usage: %s backing-file\n", argv[0]);
       exit(EXIT_FAILURE);
    }
    loopctlfd = open("/dev/loop-control", O_RDWR);
    if (loopct|fd == -1)
       errExit("open: /dev/loop-control");
    devnr = ioctl(loopctlfd, LOOP_CTL_GET_FREE);
```

```
if (devnr == -1)
        errExit("ioctl-LOOP_CTL_GET_FREE");
      sprintf(loopname, "/dev/loop%ld", devnr);
      printf("loopname = %s\n", loopname);
      loopfd = open(loopname, O_RDWR);
      if (loopfd == -1)
        errExit("open: loopname");
      backingfile = open(argv[1], O_RDWR);
      if (backingfile == -1)
        errExit("open: backing-file");
      if (ioctl(loopfd, LOOP_SET_FD, backingfile) == -1)
        errExit("ioctl-LOOP_SET_FD");
      exit(EXIT_SUCCESS);
   }
SEE ALSO
    losetup(8), mount(8)
COLOPHON
    This page is part of release 5.10 of the Linux man-pages project. A
    description of the project, information about reporting bugs, and the
    latest
           version
                     of this page, can be found at
    https://www.kernel.org/doc/man-pages/.
Linux
                      2020-11-01
                                                 LOOP(4)
```