



Rocky Enterprise Linux 9.2 Manual Pages on command 'mknod.1'

\$ man mknod.1

MKNOD(1) User Commands MKNOD(1)

NAME

mknod - make block or character special files

SYNOPSIS

mknod [OPTION]... NAME TYPE [MAJOR MINOR]

DESCRIPTION

Create the special file NAME of the given TYPE.

Mandatory arguments to long options are mandatory for short options too.

-m, --mode=MODE

set file permission bits to MODE, not a=rw - umask

-Z set the SELinux security context to default type

--context[=CTX]

like -Z, or if CTX is specified then set the SELinux or SMACK security context to CTX

--help display this help and exit

--version

output version information and exit

Both MAJOR and MINOR must be specified when TYPE is b, c, or u, and they must be omitted when TYPE is p. If MAJOR or MINOR begins with 0x or 0X, it is interpreted as hexadecimal; otherwise, if it begins with 0, as octal; otherwise, as decimal. TYPE may be:

b create a block (buffered) special file

c, u create a character (unbuffered) special file

p create a FIFO

NOTE: your shell may have its own version of mknod, which usually su?ersedes the version described here. Please refer to your shell's documentation for details about the options it supports.

AUTHOR

Written by David MacKenzie.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report any translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright ? 2020 Free Software Foundation, Inc. License GPLv3+: GNU

GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

mknod(2)

Full documentation <<https://www.gnu.org/software/coreutils/mknod>>

or available locally via: info '(coreutils) mknod invocation'