

Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'msgmerge.1'

\$ man msgmerge.1

MSGMERGE(1)

User Commands

MSGMERGE(1)

NAME

msgmerge - merge message catalog and template

SYNOPSIS

msgmerge [OPTION] def.po ref.pot

DESCRIPTION

Merges two Uniforum style .po files together. The def.po file is an existing PO file with translations which will be taken over to the newly created file as long as they still match; comments will be pre? served, but extracted comments and file positions will be discarded. The ref.pot file is the last created PO file with up-to-date source references but old translations, or a PO Template file (generally cre? ated by xgettext); any translations or comments in the file will be discarded, however dot comments and file positions will be preserved. Where an exact match cannot be found, fuzzy matching is used to produce better results.

Mandatory arguments to long options are mandatory for short options too.

Page 1/5

```
Input file location:
  def.po translations referring to old sources
  ref.pot
      references to new sources
  -D, --directory=DIRECTORY
      add DIRECTORY to list for input files search
  -C, --compendium=FILE
      additional library of message translations, may be specified
      more than once
Operation mode:
  -U, --update
      update def.po, do nothing if def.po already up to date
Output file location:
  -o, --output-file=FILE
      write output to specified file
  The results are written to standard output if no output file is speci?
  fied or if it is -.
  Output file location in update mode: The result is written back to
  def.po.
  --backup=CONTROL
      make a backup of def.po
  --suffix=SUFFIX
      override the usual backup suffix
  The version control method may be selected via the --backup option or
  through the VERSION_CONTROL environment variable. Here are the values:
  none, off
      never make backups (even if --backup is given)
  numbered, t
      make numbered backups
  existing, nil
      numbered if numbered backups exist, simple otherwise
  simple, never
```

```
The backup suffix is '~', unless set with --suffix or the SIM?
  PLE_BACKUP_SUFFIX environment variable.
Operation modifiers:
  -m, --multi-domain
      apply ref.pot to each of the domains in def.po
  --for-msgfmt
      produce output for 'msgfmt', not for a translator
  -N, --no-fuzzy-matching
      do not use fuzzy matching
  --previous
      keep previous msgids of translated messages
Input file syntax:
  -P, --properties-input
      input files are in Java .properties syntax
  --stringtable-input
      input files are in NeXTstep/GNUstep .strings syntax
Output details:
  --lang=CATALOGNAME
      set 'Language' field in the header entry
  --color
      use colors and other text attributes always
  --color=WHEN
      use colors and other text attributes if WHEN. WHEN may be 'al?
      ways', 'never', 'auto', or 'html'.
  --style=STYLEFILE
      specify CSS style rule file for --color
  -e, --no-escape
      do not use C escapes in output (default)
  -E, --escape
      use C escapes in output, no extended chars
  --force-po
      write PO file even if empty
```

-i, --indent

Page 3/5

```
indented output style
    --no-location
        suppress '#: filename:line' lines
    -n, --add-location
        preserve '#: filename:line' lines (default)
    --strict
        strict Uniforum output style
    -p, --properties-output
        write out a Java .properties file
    --stringtable-output
        write out a NeXTstep/GNUstep .strings file
    -w, --width=NUMBER
        set output page width
    --no-wrap
        do not break long message lines, longer than the output page
        width, into several lines
    -s, --sort-output
        generate sorted output
    -F, --sort-by-file
        sort output by file location
 Informative output:
    -h, --help
        display this help and exit
    -V, --version
        output version information and exit
    -v, --verbose
        increase verbosity level
    -q, --quiet, --silent
        suppress progress indicators
AUTHOR
```

Written by Peter Miller.

REPORTING BUGS

nah.gnu.org/projects/gettext> or by email to <bug-gettext@gnu.org>.

COPYRIGHT

Copyright ? 1995-2020 Free Software Foundation, Inc. License GPLv3+:

GNU GPL version 3 or later https://gnu.org/licenses/gpl.html

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

The full documentation for msgmerge is maintained as a Texinfo manual.

If the info and msgmerge programs are properly installed at your site,

the command

info msgmerge

should give you access to the complete manual.

GNU gettext-tools 20200704

July 2020

MSGMERGE(1)