



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'nftw.3'***

**\$ man nftw.3**

FTW(3)                      Linux Programmer's Manual                      FTW(3)

#### **NAME**

ftw, nftw - file tree walk

#### **SYNOPSIS**

```
#include <ftw.h>

int nftw(const char *dirpath,
        int (*fn) (const char *fpath, const struct stat *sb,
                  int typeflag, struct FTW *ftwbuf),
        int nopenfd, int flags);

#include <ftw.h>

int ftw(const char *dirpath,
        int (*fn) (const char *fpath, const struct stat *sb,
                  int typeflag),
        int nopenfd);
```

Feature Test Macro Requirements for glibc (see feature\_test\_macros(7)):

```
nftw(): _XOPEN_SOURCE >= 500
```

#### **DESCRIPTION**

nftw() walks through the directory tree that is located under the di?

rectory dirpath, and calls fn() once for each entry in the tree. By default, directories are handled before the files and subdirectories they contain (preorder traversal).

To avoid using up all of the calling process's file descriptors, nopenfd specifies the maximum number of directories that nftw() will hold open simultaneously. When the search depth exceeds this, nftw() will become slower because directories have to be closed and reopened. nftw() uses at most one file descriptor for each level in the directory tree.

For each entry found in the tree, nftw() calls fn() with four arguments: fpath, sb, typeflag, and ftwbuf. fpath is the pathname of the entry, and is expressed either as a pathname relative to the calling process's current working directory at the time of the call to nftw(), if dirpath was expressed as a relative pathname, or as an absolute pathname, if dirpath was expressed as an absolute pathname. sb is a pointer to the stat structure returned by a call to stat(2) for fpath.

The typeflag argument passed to fn() is an integer that has one of the following values:

FTW\_F fpath is a regular file.

FTW\_D fpath is a directory.

FTW\_DNR

fpath is a directory which can't be read.

FTW\_DP fpath is a directory, and FTW\_DEPTH was specified in flags. (If

FTW\_DEPTH was not specified in flags, then directories will always be visited with typeflag set to FTW\_D.) All of the files and subdirectories within fpath have been processed.

FTW\_NS The stat(2) call failed on fpath, which is not a symbolic link.

The probable cause for this is that the caller had read permission on the parent directory, so that the filename fpath could be seen, but did not have execute permission, so that the file could not be reached for stat(2). The contents of the buffer pointed to by sb are undefined.

FTW\_SL fpath is a symbolic link, and FTW\_PHYS was set in flags.

## FTW\_SLN

`fpath` is a symbolic link pointing to a nonexistent file. (This occurs only if `FTW_PHYS` is not set.) In this case the `sb` argument passed to `fn()` contains information returned by performing `lstat(2)` on the "dangling" symbolic link. (But see `BUGS`.)

The fourth argument (`ftwbuf`) that `nftw()` supplies when calling `fn()` is a pointer to a structure of type `FTW`:

```
struct FTW {  
    int base;  
    int level;  
};
```

`base` is the offset of the filename (i.e., `basename` component) in the `pathname` given in `fpath`. `level` is the depth of `fpath` in the directory tree, relative to the root of the tree (`dirpath`, which has depth 0).

To stop the tree walk, `fn()` returns a nonzero value; this value will become the return value of `nftw()`. As long as `fn()` returns 0, `nftw()` will continue either until it has traversed the entire tree, in which case it will return zero, or until it encounters an error (such as a `malloc(3)` failure), in which case it will return -1.

Because `nftw()` uses dynamic data structures, the only safe way to exit out of a tree walk is to return a nonzero value from `fn()`. To allow a signal to terminate the walk without causing a memory leak, have the handler set a global flag that is checked by `fn()`. Don't use `longjmp(3)` unless the program is going to terminate.

The `flags` argument of `nftw()` is formed by ORing zero or more of the following flags:

`FTW_ACTIONRETVAL` (since glibc 2.3.3)

If this glibc-specific flag is set, then `nftw()` handles the return value from `fn()` differently. `fn()` should return one of the following values:

`FTW_CONTINUE`

Instructs `nftw()` to continue normally.

`FTW_SKIP_SIBLINGS`

If `fn()` returns this value, then siblings of the current entry will be skipped, and processing continues in the parent.

#### FTW\_SKIP\_SUBTREE

If `fn()` is called with an entry that is a directory (typeflag is `FTW_D`), this return value will prevent objects within that directory from being passed as arguments to `fn()`. `nftw()` continues processing with the next sibling of the directory.

#### FTW\_STOP

Causes `nftw()` to return immediately with the return value `FTW_STOP`.

Other return values could be associated with new actions in the future; `fn()` should not return values other than those listed above.

The feature test macro `_GNU_SOURCE` must be defined (before including any header files) in order to obtain the definition of `FTW_ACTIONRETVAL` from `<ftw.h>`.

#### FTW\_CHDIR

If set, do a `chdir(2)` to each directory before handling its contents. This is useful if the program needs to perform some action in the directory in which `fpath` resides. (Specifying this flag has no effect on the pathname that is passed in the `fpath` argument of `fn()`.)

#### FTW\_DEPTH

If set, do a post-order traversal, that is, call `fn()` for the directory itself after handling the contents of the directory and its subdirectories. (By default, each directory is handled before its contents.)

#### FTW\_MOUNT

If set, stay within the same filesystem (i.e., do not cross mount points).

#### FTW\_PHYS

If set, do not follow symbolic links. (This is what you want.)

If not set, symbolic links are followed, but no file is reported twice.

If FTW\_PHYS is not set, but FTW\_DEPTH is set, then the function fn() is never called for a directory that would be a descendant of itself.

## ftw()

ftw() is an older function that offers a subset of the functionality of nftw(). The notable differences are as follows:

- \* ftw() has no flags argument. It behaves the same as when nftw() is called with flags specified as zero.
- \* The callback function, fn(), is not supplied with a fourth argument.
- \* The range of values that is passed via the typeflag argument supplied to fn() is smaller: just FTW\_F, FTW\_D, FTW\_DNR, FTW\_NS, and (possibly) FTW\_SL.

## RETURN VALUE

These functions return 0 on success, and -1 if an error occurs.

If fn() returns nonzero, then the tree walk is terminated and the value returned by fn() is returned as the result of ftw() or nftw().

If nftw() is called with the FTW\_ACTIONRETVAL flag, then the only non-zero value that should be used by fn() to terminate the tree walk is FTW\_STOP, and that value is returned as the result of nftw().

## VERSIONS

nftw() is available under glibc since version 2.1.

## ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

attributes(7).

??

?Interface ? Attribute ? Value ?

??

?nftw() ? Thread safety ? MT-Safe cwd ?

??

?ftw() ? Thread safety ? MT-Safe ?

??

## CONFORMING TO

POSIX.1-2001, POSIX.1-2008, SVr4, SUSv1. POSIX.1-2008 marks `ftw()` as obsolete.

## NOTES

POSIX.1-2008 notes that the results are unspecified if `fn` does not pre-serve the current working directory.

The function `nftw()` and the use of `FTW_SL` with `ftw()` were introduced in SUSv1.

In some implementations (e.g., glibc), `ftw()` will never use `FTW_SL`, on other systems `FTW_SL` occurs only for symbolic links that do not point to an existing file, and again on other systems `ftw()` will use `FTW_SL` for each symbolic link. If `fpath` is a symbolic link and `stat(2)` failed, POSIX.1-2008 states that it is undefined whether `FTW_NS` or `FTW_SL` is passed in `typeflag`. For predictable results, use `nftw()`.

## BUGS

According to POSIX.1-2008, when the `typeflag` argument passed to `fn()` contains `FTW_SLN`, the buffer pointed to by `sb` should contain information about the dangling symbolic link (obtained by calling `lstat(2)` on the link). Early glibc versions correctly followed the POSIX specification on this point. However, as a result of a regression introduced in glibc 2.4, the contents of the buffer pointed to by `sb` were undefined when `FTW_SLN` is passed in `typeflag`. (More precisely, the contents of the buffer were left unchanged in this case.) This regression was eventually fixed in glibc 2.30, so that the glibc implementation (once more) follows the POSIX specification.

## EXAMPLES

The following program traverses the directory tree under the path named in its first command-line argument, or under the current directory if no argument is supplied. It displays various information about each file. The second command-line argument can be used to specify characters that control the value assigned to the `flags` argument when calling `nftw()`.

## Program source

```
#define _XOPEN_SOURCE 500

#include <ftw.h>

#include <stdio.h>

#include <stdlib.h>

#include <string.h>

#include <stdint.h>

static int

display_info(const char *fpath, const struct stat *sb,

             int tflag, struct FTW *ftwbuf)

{

    printf("%-3s %2d ",

           (tflag == FTW_D) ? "d" : (tflag == FTW_DNR) ? "dnr" :

           (tflag == FTW_DP) ? "dp" : (tflag == FTW_F) ? "f" :

           (tflag == FTW_NS) ? "ns" : (tflag == FTW_SL) ? "sl" :

           (tflag == FTW_SLN) ? "sln" : "???",

           ftwbuf->level);

    if (tflag == FTW_NS)

        printf("-----");

    else

        printf("%7jd", (intmax_t) sb->st_size);

    printf("  %-40s %d %s\n",

           fpath, ftwbuf->base, fpath + ftwbuf->base);

    return 0;      /* To tell nftw() to continue */

}

int

main(int argc, char *argv[])

{

    int flags = 0;

    if (argc > 2 && strchr(argv[2], 'd') != NULL)

        flags |= FTW_DEPTH;

    if (argc > 2 && strchr(argv[2], 'p') != NULL)

        flags |= FTW_PHYS;
```

```
if (nftw((argc < 2) ? "." : argv[1], display_info, 20, flags)
    == -1) {
    perror("nftw");
    exit(EXIT_FAILURE);
}
exit(EXIT_SUCCESS);
}
```

#### SEE ALSO

stat(2), fts(3), readdir(3)

#### COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2020-06-09

FTW(3)