



Rocky Enterprise Linux 9.2 Manual Pages on command 'nvme-wdc-vs-hw-rev-log.1'

\$ man nvme-wdc-vs-hw-rev-log.1

NVME-WDC-VS-HW-R(1) NVMe Manual NVME-WDC-VS-HW-R(1)

NAME

nvme-wdc-vs-hw-rev-log - Send NVMe WDC vs-hw-rev-log Vendor Unique
Command, return result

SYNOPSIS

```
nvme wdc vs-hw-rev-log <device> [--output-format=<normal|json> -o <normal|json>]
                                [--namespace-id=<nsid> | -n <nsid>]
```

DESCRIPTION

For the NVMe device given, retrieves and formats the Vendor Unique WDC
hw revision log page.

The <device> parameter is mandatory and may be either the NVMe
character device (ex: /dev/nvme0) or block device (ex: /dev/nvme0n1).

This will only work on WDC devices supporting this feature. Results for
any other device are undefined.

On success it returns 0, error code otherwise.

OPTIONS

-o <format>, --output-format=<format>

Set the reporting format to normal, or json. Only one output format

can be used at a time. Default is normal.

-n <nsid>, --namespace-id=<nsid>

Sets the command's nsid value to the given nsid. Defaults to

0xffffffff if not given. This option may not affect anything

depending on the log page, which may or may not be specific to a namespace.

EXAMPLES

? Has the program issue WDC vs-hw-rev-log plugin Command :

```
# nvme wdc vs-hw-rev-log /dev/nvme0
```

NVME

Part of the nvme-user suite.

NVMe	06/23/2023	NVME-WDC-VS-HW-R(1)
------	------------	---------------------