



Rocky Enterprise Linux 9.2 Manual Pages on command 'ostree-admin-deploy.1'

\$ man ostree-admin-deploy.1

OSTREE ADMIN DEPLOY(1) ostree admin deploy OSTREE ADMIN DEPLOY(1)

NAME

ostree-admin-deploy - Checkout a revision as the new default deployment

SYNOPSIS

ostree admin deploy [OPTIONS...] {REFSPEC}

DESCRIPTION

Takes a commit or revision REFSPEC, and queues the new deployment as default upon reboot.

OPTIONS

--os="STATEROOT"

Use a different operating system root than the current one.

--origin-file="FILENAME"

Use FILENAME as the origin, which is where OSTree will look for

updated versions of the tree.

`--retain`

Do not delete previous deployment.

`--retain-pending`

Do not delete pending deployments.

`--retain-rollback`

Do not delete rollback deployments.

`--not-as-default`

Append rather than prepend new deployment.

`--karg-proc-cmdline`

Import current `/proc/cmdline`.

`--karg="NAME=VALUE"`

Set kernel argument, like `root=/dev/sda1`; this overrides any earlier argument with the same name.

`--karg-append="NAME=VALUE"`

Append kernel argument; useful with e.g. `console=` that can be used multiple times.

EXAMPLE

`$ ostree admin status`

```
* gnome-ostree 67e382b11d213a402a5313e61cbc69dfd5ab93cb07.0
  origin refspeg: gnome-ostree/buildmain/x86_64-runtime
gnome-ostree ce19c41036cc45e49b0cecf6b157523c2105c4de1ce3.0
  origin refspeg: gnome-ostree/buildmain/x86_64-runtime
```

\$ ostree admin deploy gnome-ostree/buildmain/x86_64-runtime

ostadmin: Creating deployment

/ostree/deploy/gnome-ostree/deploy/7e382b11d213a402a5313e61cbc69dfd5ab93cb07.1

ostadmin: Processing /etc: 3 modified, 0 removed, 29 added

Transaction complete: bootconfig swap: no deployment count change: 0)

\$ ostree admin status

gnome-ostree 67e382b11d213a402a5313e61cbc69dfd5ab93cb07.1

origin refspect: gnome-ostree/buildmain/x86_64-runtime

* gnome-ostree 67e382b11d213a402a5313e61cbc69dfd5ab93cb07.0

origin refspect: gnome-ostree/buildmain/x86_64-runtime

OSTree

OSTREE ADMIN DEPLOY(1)