



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'ostree-config.1'***

***\$ man ostree-config.1***

OSTREE CONFIG(1)            ostree config            OSTREE CONFIG(1)

NAME

ostree-config - Change configuration settings

SYNOPSIS

ostree config get {GROUPNAME.KEYNAME}

ostree config get {--group=GROUPNAME} {KEYNAME}

ostree config set {GROUPNAME.KEYNAME} {VALUE}

ostree config set {--group=GROUPNAME} {KEYNAME} {VALUE}

ostree config unset {GROUPNAME.KEYNAME}

ostree config unset {--group=GROUPNAME} {KEYNAME}

## DESCRIPTION

- ? `ostree config get` displays the value of `KEYNAME` in the group `GROUPNAME`
- ? `ostree config set` sets the value of `KEYNAME` in the group `GROUPNAME` to `VALUE`.
- ? `ostree config unset` removes the key `KEYNAME` from the group `GROUPNAME` so that OSTree uses the default value for it. It is not an error for the specified `GROUPNAME` or `KEYNAME` not to exist.

## EXAMPLE

```
$ ostree config get core.mode
```

```
bare
```

```
$ ostree config set --group='remote "myremote"' url  
http://example.com/repo
```

```
$ ostree config unset core.lock-timeout-secs
```

OSTree

OSTREE CONFIG(1)