



***Rocky Enterprise Linux 9.2 Manual Pages on command 'paperconfig.8'***

***\$ man paperconfig.8***

PAPERCONFIG(8)      Linux Administrator's Manual      PAPERCONFIG(8)

**NAME**

paperconfig - configure the system default paper size

**SYNOPSIS**

paperconfig [ -v,--version ] [ -h,--help ] [ -p, --paper papername |  
--force ]

**DESCRIPTION**

paperconfig sets the system (or default) paper to be used by tools us?  
ing the papersize file. It can either ask interactively for the paper  
to use or be called non-interactively by scripts.

When the paper size has been changed, paperconfig notifies other pack?  
ages of the change by running the scripts in the /etc/libpaper.d direc?  
tory.

## OPTIONS

`-v,--version`

Print the version of paperconfig and exit.

`-h,--help`

Print help about usage and exit.

`-p, --paper papername`

Use papername if possible. If papername is not a valid paper, print an error message and exit.

`--force`

Force interactive selection of the system paper even if the actual paper is a valid one.

## ENVIRONMENT

**PAPERCONF** Full path to a file containing the paper size to use; this file will be rewritten with the system paper size.

## FILES

**/etc/papersize** Contains the name of the system-wide default paper size to be used if the **PAPERSIZE** variable is not set.

**/etc/libpaper.d** Directory of scripts to run after the paper size has been changed. This package puts no scripts here, but other packages may. **run-parts** is used to run the scripts, therefore their names must comply with **run-part's** naming requirements.

## AUTHOR

Yves Arrouye <arrouye@debian.org>

## SEE ALSO

[paperconf\(1\)](#)

[papersize\(5\)](#)

Debian/Linux

5 January 2005

PAPERCONFIG(8)