



Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-container-umount.1'

\$ man podman-container-umount.1

podman-umount(1) General Commands Manual podman-umount(1)

NAME

podman-umount - Unmount a working container's root filesystem

SYNOPSIS

podman unmount [options] container [...]

podman umount [options] container [...]

podman container unmount [options] container [...]

podman container umount [options] container [...]

DESCRIPTION

Unmounts the specified containers' root file system, if no other processes are using it.

Container storage increments a mount counter each time a container is

mounted. When a container is unmounted, the mount counter is decremented,

and the container's root filesystem is physically unmounted

only when the mount counter reaches zero indicating no other processes

are using the mount. An unmount can be forced with the --force flag.

Note: Podman can be used to unmount Podman containers as well as external

containers. External containers are containers created in containers

tainer/storage by other tools like Buildah and CRI-O.

OPTIONS

`--all, -a`

All of the currently mounted containers will be unmounted.

`--force, -f`

Force the unmounting of specified containers' root file system, even if other processes have mounted it.

Note: This could cause other processes that are using the file system to fail, as the mount point could be removed without their knowledge.

`--latest, -l`

Instead of providing the container name or ID, use the last created container. Note: the last started container could be from other users of Podman on the host machine. (This option is not available with the remote Podman client, including Mac and Windows (excluding WSL2) machines)

EXAMPLE

Unmount container with a given ID

```
podman container unmount containerID
```

Unmount multiple containers with given IDs

```
podman unmount containerID1 containerID2 containerID3
```

Unmount all containers

```
podman unmount --all
```

SEE ALSO

`podman(1)`, `podman-mount(1)`, `podman-image-mount(1)`

`podman-unmount(1)`