



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-logout.1'***

### ***\$ man podman-logout.1***

podman-logout(1)      General Commands Manual      podman-logout(1)

#### NAME

podman-logout - Logout of a container registry

#### SYNOPSIS

podman logout [options] registry

#### DESCRIPTION

podman logout logs out of a specified registry server by deleting the cached credentials stored in the auth.json file. If the registry is not specified, the first registry under [registries.search] from registries.conf will be used. The path of the authentication file can be overridden by the user by setting the authfile flag. The default path used is \${XDG\_RUNTIME\_DIR}/containers/auth.json. For more details about format and configurations of the auth.json file, please refer to containers-auth.json(5) All the cached credentials can be removed by setting the all flag.

podman [GLOBAL OPTIONS]

podman logout [GLOBAL OPTIONS]

podman logout [OPTIONS] REGISTRY [GLOBAL OPTIONS]

## OPTIONS

`--all, -a`

Remove the cached credentials for all registries in the auth file

`--authfile=path`

Path of the authentication file. Default is `${XDG_RUNTIME_DIR}/containers/auth.json`, which is set using `podman login`. If the authorization state is not found there, `$HOME/.docker/config.json` is checked, which is set using `docker login`.

Note: There is also the option to override the default path of the authentication file by setting the `REGISTRY_AUTH_FILE` environment variable. This can be done with `export REGISTRY_AUTH_FILE=path`.

`--help, -h`

Print usage statement

## EXAMPLES

```
$ podman logout docker.io
```

Remove login credentials for `https://registry-1.docker.io/v2/`

```
$ podman logout --authfile authdir/myauths.json docker.io
```

Remove login credentials for `https://registry-1.docker.io/v2/`

```
$ podman logout --all
```

Remove login credentials for all registries

## SEE ALSO

`podman(1)`, `podman-login(1)`, `containers-auth.json(5)`

## HISTORY

August 2017, Originally compiled by Urvashi Mohnani [umohnani@redhat.com](mailto:umohnani@redhat.com)  
[?mailto:umohnani@redhat.com?](mailto:umohnani@redhat.com)

`podman-logout(1)`