



Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-machine-set.1'

\$ man podman-machine-set.1

podman-machine-set(1) General Commands Manual podman-machine-set(1)

NAME

podman-machine-set - Sets a virtual machine setting

SYNOPSIS

podman machine set [options] [name]

DESCRIPTION

Change a machine setting.

Rootless only.

OPTIONS

--cpus=number

Number of CPUs. Only supported for QEMU machines.

--disk-size=number

Size of the disk for the guest VM in GB. Can only be increased. Only supported for QEMU machines.

--help

Print usage statement.

--memory, -m=number

Memory (in MB). Only supported for QEMU machines.

`--rootful`

Whether this machine should prefer rootful (true) or rootless (false) container execution. This option will also update the current podman remote connection default if it is currently pointing at the specified machine name (or podman-machine-default if no name is specified). Unlike [podman system connection default] this option will also make the API socket, if available, forward to the rootful/rootless socket in the VM.

EXAMPLES

To switch the default VM podman-machine-default from rootless to rootful:

```
$ podman machine set --rootful
```

or more explicitly:

```
$ podman machine set --rootful=true
```

To switch the default VM podman-machine-default from rootful to rootless:

```
$ podman machine set --rootful=false
```

To switch the VM myvm from rootless to rootful:

```
$ podman machine set --rootful myvm
```

SEE ALSO

podman(1), podman-machine(1)

HISTORY

February 2022, Originally compiled by Jason Greene jason.greene@redhat.com

podman-machine-set(1)