



Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-rmi.1'

\$ man podman-rmi.1

podman-rmi(1) General Commands Manual podman-rmi(1)

NAME

podman-rmi - Removes one or more locally stored images

SYNOPSIS

podman rmi [options] image [...]

podman image rm [options] image [...]

DESCRIPTION

Removes one or more locally stored images. Passing an argument image deletes it, along with any of its dangling parent images. A dangling image is an image without a tag and without being referenced by another image.

Note: To delete an image from a remote registry, use the skopeo delete command. Some registries do not allow users to delete an image via a CLI remotely.

OPTIONS

--all, -a

Remove all images in the local storage.

--force, -f

This option will cause podman to remove all containers that are using the image before removing the image from the system.

`--ignore, -i`

If a specified image does not exist in the local storage, ignore it and do not throw an error.

`--no-prune`

This options will not remove dangling parents of specified image

Remove an image by its short ID

```
$ podman rmi c0ed59d05ff7
```

Remove an image and its associated containers.

```
$ podman rmi --force imageID
```

Remove multiple images by their shortened IDs.

```
$ podman rmi c4dfb1609ee2 93fd78260bd1 c0ed59d05ff7
```

Remove all images and containers.

```
$ podman rmi -a -f
```

Remove an absent image with and without the `--ignore` flag.

```
$ podman rmi --ignore nothing
```

```
$ podman rmi nothing
```

```
Error: nothing: image not known
```

Exit Status

0 All specified images removed

1 One of the specified images did not exist, and no other failures

2 One of the specified images has child images or is being used by a container

125 The command fails for any other reason

SEE ALSO

`podman(1)`, `skopeo-delete(1)`

HISTORY

March 2017, Originally compiled by Dan Walsh dwalsh@redhat.com

[?mailto:dwalsh@redhat.com?](mailto:dwalsh@redhat.com)

`podman-rmi(1)`