



Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-volume-ls.1'

\$ man podman-volume-ls.1

podman-volume-ls(1) General Commands Manual podman-volume-ls(1)

NAME

podman-volume-ls - List all the available volumes

SYNOPSIS

podman volume ls [options]

DESCRIPTION

Lists all the volumes that exist. The output can be filtered using the --filter flag and can be formatted to either JSON or a Go template using the --format flag. Use the --quiet flag to print only the volume names.

OPTIONS

--filter, -f=filter

Volumes can be filtered by the following attributes:

??

?Filter ? Description ?

??

?dangling ? [Dangling] Matches all ?

? ? volumes not referenced by ?

? ? any containers ?

??

?driver ? [Driver] Matches volumes ?

? ? based on their driver ?

??

?label ? [Key] or [Key=Value] Label ?

? ? assigned to a volume ?

??

?name ? [Name] Volume name (accepts regex) ?

? ? cepts regex) ?

??

?opt ? Matches a storage driver ?

? ? options ?

??

?scope ? Filters volume by scope ?

??

?until ? Only remove volumes created before given time ?

? ? ated before given time ?

? ? stamp ?

??

- format=format
Format volume output using Go template.
- help
Print usage statement.
- noheading, -n
Omit the table headings from the listing.
- quiet, -q
Print volume output in quiet mode. Only print the volume names.

EXAMPLES

```
$ podman volume ls
$ podman volume ls --format json
$ podman volume ls --format "{{.Driver}} {{.Scope}}"
$ podman volume ls --filter name=foo,label=blue
```

```
$ podman volume ls --filter label=key=value
```

SEE ALSO

podman(1), podman-volume(1)

HISTORY

November 2018, Originally compiled by Urvashi Mohnani umohnani@redhat.com

umohnani@redhat.com

podman-volume-ls(1)