



### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'poll.2'***

**\$ man poll.2**

POLL(2)                      Linux Programmer's Manual                      POLL(2)

#### NAME

poll, ppoll - wait for some event on a file descriptor

#### SYNOPSIS

```
#include <poll.h>

int poll(struct pollfd *fds, nfds_t nfds, int timeout);

#define _GNU_SOURCE      /* See feature_test_macros(7) */

#include <signal.h>

#include <poll.h>

int ppoll(struct pollfd *fds, nfds_t nfds,

          const struct timespec *tmo_p, const sigset_t *sigmask);
```

#### DESCRIPTION

poll() performs a similar task to select(2): it waits for one of a set of file descriptors to become ready to perform I/O. The Linux-specific epoll(7) API performs a similar task, but offers features beyond those found in poll().

The set of file descriptors to be monitored is specified in the fds argument, which is an array of structures of the following form:

```

struct pollfd {
    int fd;      /* file descriptor */
    short events; /* requested events */
    short revents; /* returned events */
};

```

The caller should specify the number of items in the fds array in nfd.

The field fd contains a file descriptor for an open file. If this field is negative, then the corresponding events field is ignored and the revents field returns zero. (This provides an easy way of ignoring a file descriptor for a single poll() call: simply negate the fd field.

Note, however, that this technique can't be used to ignore file descriptor 0.)

The field events is an input parameter, a bit mask specifying the events the application is interested in for the file descriptor fd.

This field may be specified as zero, in which case the only events that can be returned in revents are POLLHUP, POLLERR, and POLLNVAL (see below).

The field revents is an output parameter, filled by the kernel with the events that actually occurred. The bits returned in revents can include any of those specified in events, or one of the values POLLERR, POLLHUP, or POLLNVAL. (These three bits are meaningless in the events field, and will be set in the revents field whenever the corresponding condition is true.)

If none of the events requested (and no error) has occurred for any of the file descriptors, then poll() blocks until one of the events occurs.

The timeout argument specifies the number of milliseconds that poll() should block waiting for a file descriptor to become ready. The call will block until either:

- ? a file descriptor becomes ready;
- ? the call is interrupted by a signal handler; or
- ? the timeout expires.

Note that the timeout interval will be rounded up to the system clock

granularity, and kernel scheduling delays mean that the blocking interval may be overrun by a small amount. Specifying a negative value in timeout means an infinite timeout. Specifying a timeout of zero causes poll() to return immediately, even if no file descriptors are ready.

The bits that may be set/returned in events and revents are defined in <poll.h>:

POLLIN There is data to read.

POLLPRI

There is some exceptional condition on the file descriptor.

Possibilities include:

? There is out-of-band data on a TCP socket (see tcp(7)).

? A pseudoterminal master in packet mode has seen a state change on the slave (see ioctl\_tty(2)).

? A cgroup.events file has been modified (see cgroups(7)).

POLLOUT

Writing is now possible, though a write larger than the available space in a socket or pipe will still block (unless O\_NONBLOCK is set).

POLLRDHUP (since Linux 2.6.17)

Stream socket peer closed connection, or shut down writing half of connection. The \_GNU\_SOURCE feature test macro must be defined (before including any header files) in order to obtain this definition.

POLLERR

Error condition (only returned in revents; ignored in events).

This bit is also set for a file descriptor referring to the write end of a pipe when the read end has been closed.

POLLHUP

Hang up (only returned in revents; ignored in events). Note that when reading from a channel such as a pipe or a stream socket, this event merely indicates that the peer closed its end of the channel. Subsequent reads from the channel will return 0 (end of file) only after all outstanding data in the channel has

been consumed.

## POLLNVAL

Invalid request: fd not open (only returned in revents; ignored in events).

When compiling with `_XOPEN_SOURCE` defined, one also has the following, which convey no further information beyond the bits listed above:

## POLLRDNORM

Equivalent to `POLLIN`.

## POLLRDBAND

Priority band data can be read (generally unused on Linux).

## POLLWRNORM

Equivalent to `POLLOUT`.

## POLLWRBAND

Priority data may be written.

Linux also knows about, but does not use `POLLMSG`.

## ppoll()

The relationship between `poll()` and `ppoll()` is analogous to the relationship between `select(2)` and `pselect(2)`: like `pselect(2)`, `ppoll()` allows an application to safely wait until either a file descriptor becomes ready or until a signal is caught.

Other than the difference in the precision of the timeout argument, the following `ppoll()` call:

```
ready = ppoll(&fds, nfd, tmo_p, &sigmask);
```

is nearly equivalent to atomically executing the following calls:

```
sigset_t origmask;
```

```
int timeout;
```

```
timeout = (tmo_p == NULL) ? -1 :
```

```
(tmo_p->tv_sec * 1000 + tmo_p->tv_nsec / 1000000);
```

```
pthread_sigmask(SIG_SETMASK, &sigmask, &origmask);
```

```
ready = poll(&fds, nfd, timeout);
```

```
pthread_sigmask(SIG_SETMASK, &origmask, NULL);
```

The above code segment is described as nearly equivalent because whereas a negative timeout value for `poll()` is interpreted as an infinity

nite timeout, a negative value expressed in `*tmo_p` results in an error from `ppoll()`.

See the description of `pselect(2)` for an explanation of why `ppoll()` is necessary.

If the `sigmask` argument is specified as `NULL`, then no signal mask manipulation is performed (and thus `ppoll()` differs from `poll()` only in the precision of the timeout argument).

The `tmo_p` argument specifies an upper limit on the amount of time that `ppoll()` will block. This argument is a pointer to a structure of the following form:

```
struct timespec {
    long   tv_sec;      /* seconds */
    long   tv_nsec;     /* nanoseconds */
};
```

If `tmo_p` is specified as `NULL`, then `ppoll()` can block indefinitely.

## RETURN VALUE

On success, `poll()` returns a nonnegative value which is the number of elements in the `pollfds` whose `revents` fields have been set to a nonzero value (indicating an event or an error). A return value of zero indicates that the system call timed out before any file descriptors became read.

On error, `-1` is returned, and `errno` is set to indicate the cause of the error.

## ERRORS

**EFAULT** `fds` points outside the process's accessible address space. The array given as argument was not contained in the calling program's address space.

**EINTR** A signal occurred before any requested event; see `signal(7)`.

**EINVAL** The `nfds` value exceeds the `RLIMIT_NOFILE` value.

**EINVAL** (`ppoll()`) The timeout value expressed in `*tp` is invalid (negative).

**ENOMEM** Unable to allocate memory for kernel data structures.

## VERSIONS

The poll() system call was introduced in Linux 2.1.23. On older kernels that lack this system call, the glibc poll() wrapper function provides emulation using select(2).

The ppoll() system call was added to Linux in kernel 2.6.16. The ppoll() library call was added in glibc 2.4.

## CONFORMING TO

poll() conforms to POSIX.1-2001 and POSIX.1-2008. ppoll() is Linux-specific.

## NOTES

The operation of poll() and ppoll() is not affected by the O\_NONBLOCK flag.

On some other UNIX systems, poll() can fail with the error EAGAIN if the system fails to allocate kernel-internal resources, rather than ENOMEM as Linux does. POSIX permits this behavior. Portable programs may wish to check for EAGAIN and loop, just as with EINTR.

Some implementations define the nonstandard constant INFTIM with the value -1 for use as a timeout for poll(). This constant is not provided in glibc.

For a discussion of what may happen if a file descriptor being monitored by poll() is closed in another thread, see select(2).

## C library/kernel differences

The Linux ppoll() system call modifies its tmo\_p argument. However, the glibc wrapper function hides this behavior by using a local variable for the timeout argument that is passed to the system call. Thus, the glibc ppoll() function does not modify its tmo\_p argument.

The raw ppoll() system call has a fifth argument, size\_t sigsetsize, which specifies the size in bytes of the sigmask argument. The glibc ppoll() wrapper function specifies this argument as a fixed value (equal to sizeof(kernel\_sigset\_t)). See sigprocmask(2) for a discussion on the differences between the kernel and the libc notion of the sigset.

## BUGS

See the discussion of spurious readiness notifications under the BUGS

section of select(2).

## EXAMPLES

The program below opens each of the files named in its command-line arguments and monitors the resulting file descriptors for readiness to read (POLLIN). The program loops, repeatedly using poll() to monitor the file descriptors, printing the number of ready file descriptors on return. For each ready file descriptor, the program:

- ? displays the returned revents field in a human-readable form;
- ? if the file descriptor is readable, reads some data from it, and displays that data on standard output; and
- ? if the file descriptors was not readable, but some other event occurred (presumably POLLHUP), closes the file descriptor.

Suppose we run the program in one terminal, asking it to open a FIFO:

```
$ mkfifo myfifo
$ ./poll_input myfifo
```

In a second terminal window, we then open the FIFO for writing, write some data to it, and close the FIFO:

```
$ echo aaaaabbbbbccccc > myfifo
```

In the terminal where we are running the program, we would then see:

```
Opened "myfifo" on fd 3
About to poll()
Ready: 1
fd=3; events: POLLIN POLLHUP
read 10 bytes: aaaaabbbbb
About to poll()
Ready: 1
fd=3; events: POLLIN POLLHUP
read 6 bytes: ccccc
About to poll()
Ready: 1
fd=3; events: POLLHUP
closing fd 3
```

All file descriptors closed; bye

In the above output, we see that poll() returned three times:

? On the first return, the bits returned in the revents field were

POLLIN, indicating that the file descriptor is readable, and POLLHUP, indicating that the other end of the FIFO has been closed. The program then consumed some of the available input.

? The second return from poll() also indicated POLLIN and POLLHUP; the program then consumed the last of the available input.

? On the final return, poll() indicated only POLLHUP on the FIFO, at which point the file descriptor was closed and the program terminated.

#### Program source

```
/* poll_input.c

Licensed under GNU General Public License v2 or later.

*/

#include <poll.h>
#include <fcntl.h>
#include <sys/types.h>
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>

#define errExit(msg) do { perror(msg); exit(EXIT_FAILURE); \
                      } while (0)

int
main(int argc, char *argv[])
{
    int nfds, num_open_fds;
    struct pollfd *pfd;

    if (argc < 2) {
        fprintf(stderr, "Usage: %s file...\n", argv[0]);
        exit(EXIT_FAILURE);
    }

    num_open_fds = nfds = argc - 1;
    pfd = calloc(nfds, sizeof(struct pollfd));
```



```

if (pfds == NULL)
    errExit("malloc");

/* Open each file on command line, and add it 'pfds' array */
for (int j = 0; j < nfds; j++) {
    pfd[j].fd = open(argv[j + 1], O_RDONLY);
    if (pfd[j].fd == -1)
        errExit("open");
    printf("Opened \"%s\" on fd %d\n", argv[j + 1], pfd[j].fd);
    pfd[j].events = POLLIN;
}

/* Keep calling poll() as long as at least one file descriptor is
   open */
while (num_open_fds > 0) {
    int ready;
    printf("About to poll()\n");
    ready = poll(pfds, nfds, -1);
    if (ready == -1)
        errExit("poll");
    printf("Ready: %d\n", ready);
    /* Deal with array returned by poll() */
    for (int j = 0; j < nfds; j++) {
        char buf[10];
        if (pfd[j].revents != 0) {
            printf(" fd=%d; events: %s%s%s\n", pfd[j].fd,
                (pfd[j].revents & POLLIN) ? "POLLIN " : "",
                (pfd[j].revents & POLLHUP) ? "POLLHUP " : "",
                (pfd[j].revents & POLLERR) ? "POLLERR " : "");
            if (pfd[j].revents & POLLIN) {
                ssize_t s = read(pfd[j].fd, buf, sizeof(buf));
                if (s == -1)
                    errExit("read");
                printf(" read %zd bytes: %.s\n",
                    s, (int) s, buf);
            }
        }
    }
}

```

```

    } else {          /* POLLERR | POLLHUP */
        printf("  closing fd %d\n", pfds[j].fd);
        if (close(pfds[j].fd) == -1)
            errExit("close");
        num_open_fds--;
    }
}

}

}

printf("All file descriptors closed; bye\n");
exit(EXIT_SUCCESS);
}

```

#### SEE ALSO

restart\_syscall(2), select(2), select\_tut(2), epoll(7), time(7)

#### COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2020-04-11

POLL(2)