



Rocky Enterprise Linux 9.2 Manual Pages on command 'pthread_cleanup_push_defer_np.3'

\$ man pthread_cleanup_push_defer_np.3

PTHREAD_CLEANUP_PUSH_DEFER_Linux Programmer's PTHREAD_CLEANUP_PUSH_DEFER_NP(3)

NAME

pthread_cleanup_push_defer_np, pthread_cleanup_pop_restore_np - push

and pop thread cancellation clean-up handlers while saving cancelabil?

ity type

SYNOPSIS

```
#include <pthread.h>
```

```
void pthread_cleanup_push_defer_np(void (*routine)(void *),  
                                   void *arg);
```

```
void pthread_cleanup_pop_restore_np(int execute);
```

Compile and link with -pthread.

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```
pthread_cleanup_push_defer_np(), pthread_cleanup_pop_defer_np():
```

```
_GNU_SOURCE
```

DESCRIPTION

These functions are the same as pthread_cleanup_push(3) and

pthread_cleanup_pop(3), except for the differences noted on this page.

Like pthread_cleanup_push(3), pthread_cleanup_push_defer_np() pushes

routine onto the thread's stack of cancellation clean-up handlers. In addition, it also saves the thread's current cancelability type, and sets the cancelability type to "deferred" (see `pthread_setcanceltype(3)`); this ensures that cancellation clean-up will occur even if the thread's cancelability type was "asynchronous" before the call. Like `pthread_cleanup_pop(3)`, `pthread_cleanup_pop_restore_np()` pops the top-most clean-up handler from the thread's stack of cancellation clean-up handlers. In addition, it restores the thread's cancelability type to its value at the time of the matching `pthread_cleanup_push_defer_np()`.

The caller must ensure that calls to these functions are paired within the same function, and at the same lexical nesting level. Other restrictions apply, as described in `pthread_cleanup_push(3)`.

This sequence of calls:

```
pthread_cleanup_push_defer_np(routine, arg);  
pthread_cleanup_pop_restore_np(execute);
```

is equivalent to (but shorter and more efficient than):

```
int oldtype;  
pthread_cleanup_push(routine, arg);  
pthread_setcanceltype(PTHREAD_CANCEL_DEFERRED, &oldtype);  
...  
pthread_setcanceltype(oldtype, NULL);  
pthread_cleanup_pop(execute);
```

CONFORMING TO

These functions are nonstandard GNU extensions; hence the suffix "_np" (nonportable) in the names.

SEE ALSO

`pthread_cancel(3)`, `pthread_cleanup_push(3)`, `pthread_setcancelstate(3)`,
`pthread_testcancel(3)`, `threads(7)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at

<https://www.kernel.org/doc/man-pages/>.

Linux

2017-09-15 PTHREAD_CLEANUP_PUSH_DEFER_NP(3)