



*Full credit is given to the above companies including the OS that this PDF file was generated!*

***Rocky Enterprise Linux 9.2 Manual Pages on command 'pthread\_mutexattr\_destroy.3'***

**\$ man pthread\_mutexattr\_destroy.3**

PTHREAD\_MUTEXATTR\_INIT(3) Linux Programmer's Manual PTHREAD\_MUTEXATTR\_INIT(3)

#### NAME

pthread\_mutexattr\_init, pthread\_mutexattr\_destroy - initialize and de?

stroy a mutex attributes object

#### SYNOPSIS

```
#include <pthread.h>
```

```
int pthread_mutexattr_init(pthread_mutexattr_t *attr);
```

```
int pthread_mutexattr_destroy(pthread_mutexattr_t *attr);
```

Compile and link with -pthread.

#### DESCRIPTION

The pthread\_mutexattr\_init() function initializes the mutex attributes

object pointed to by attr with default values for all attributes de?

fined by the implementation.

The results of initializing an already initialized mutex attributes ob?

ject are undefined.

The pthread\_mutexattr\_destroy() function destroys a mutex attribute ob?

ject (making it uninitialized). Once a mutex attributes object has

been destroyed, it can be reinitialized with pthread\_mutexattr\_init().

The results of destroying an uninitialized mutex attributes object are undefined.

## RETURN VALUE

On success, these functions return 0. On error, they return a positive error number.

## CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

## NOTES

Subsequent changes to a mutex attributes object do not affect mutex that have already been initialized using that object.

## SEE ALSO

`pthread_mutex_init(3)`, `pthread_mutexattr_getpshared(3)`,

`pthread_mutexattr_getrobust(3)`, `pthreads(7)`

## COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at  
<https://www.kernel.org/doc/man-pages/>.