



Rocky Enterprise Linux 9.2 Manual Pages on command 'qfcvt.3'

\$ man qfcvt.3

QECVT(3) Linux Programmer's Manual QECVT(3)

NAME

qecvt, qfcvt, qgcvt - convert a floating-point number to a string

SYNOPSIS

```
#include <stdlib.h>
```

```
char *qecvt(long double number, int ndigits, int *decpt, int *sign);
```

```
char *qfcvt(long double number, int ndigits, int *decpt, int *sign);
```

```
char *qgcvt(long double number, int ndigit, char *buf);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```
qecvt(), qfcvt(), qgcvt(): _SVID_SOURCE
```

DESCRIPTION

The functions `qecvt()`, `qfcvt()`, and `qgcvt()` are identical to `ecvt(3)`, `fcvt(3)`, and `gcvt(3)` respectively, except that they use a `long double` argument number. See `ecvt(3)` and `gcvt(3)`.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

Interface	Attribute	Value	
<pre> qecvt() Thread safety MT-Unsafe race:qecvt qfcvt() Thread safety MT-Unsafe race:qfcvt qgcvt() Thread safety MT-Safe </pre>			

CONFORMING TO

SVr4. Not seen in most common UNIX implementations, but occurs in SunOS. Supported by glibc.

NOTES

These functions are obsolete. Instead, snprintf(3) is recommended.

SEE ALSO

ecvt(3), ecvt_r(3), gcvt(3), sprintf(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.