



Rocky Enterprise Linux 9.2 Manual Pages on command 'rmdir.1'

\$ man rmdir.1

RMDIR(1) User Commands RMDIR(1)

NAME

rmdir - remove empty directories

SYNOPSIS

rmdir [OPTION]... DIRECTORY...

DESCRIPTION

Remove the DIRECTORY(ies), if they are empty.

--ignore-fail-on-non-empty

ignore each failure that is solely because a directory
is non-empty

-p, --parents

remove DIRECTORY and its ancestors; e.g., 'rmdir -p a/b/c' is
similar to 'rmdir a/b/c a/b a'

-v, --verbose

output a diagnostic for every directory processed

--help display this help and exit

--version

output version information and exit

AUTHOR

Written by David MacKenzie.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report any translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright ? 2020 Free Software Foundation, Inc. License GPLv3+: GNU

GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

rmdir(2)

Full documentation <<https://www.gnu.org/software/coreutils/rmdir>>

or available locally via: info '(coreutils) rmdir invocation'

GNU coreutils 8.32

January 2023

RMDIR(1)