



### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'rpmdb.8'***

**\$ man rpmdb.8**

RPMDDB(8)                      System Manager's Manual                      RPMDDB(8)

#### NAME

rpmdb - RPM Database Tool

#### SYNOPSIS

rpm {--initdb|--rebuilddb}

#### DESCRIPTION

The general form of an rpm rebuild database command is

rpm {--initdb|--rebuilddb} [-v] [--dbpath DIRECTORY] [--root DIRECTORY]

Use --initdb to create a new database if one doesn't already exist (existing database is not overwritten), use --rebuilddb to rebuild the database indices from the installed package headers.

#### SEE ALSO

popt(3),  
rpm(8),  
rpmkeys(8),  
rpmsign(8),  
rpm2cpio(8),  
rpmbuild(8),

rpmspec(8),

rpm --help - as rpm supports customizing the options via popt aliases

it's impossible to guarantee that what's described in the manual  
matches what's available.

<http://www.rpm.org/> <URL:<http://www.rpm.org/>>

## AUTHORS

Marc Ewing <marc@redhat.com>

Jeff Johnson <jbj@redhat.com>

Erik Troan <ewt@redhat.com>

Panu Matilainen <pmatilai@redhat.com>

Red Hat, Inc

29 June 2010

RPMDDB(8)