

Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 's390_pci_mmio_write.2'

\$ man s390_pci_mmio_write.2

S390_PCI_MMIO_WRITE(2)

S390_PCI_MMIO_WRITE(2)

NAME

s390_pci_mmio_write, s390_pci_mmio_read - transfer data to/from PCI

System Calls Manual

MMIO memory page

SYNOPSIS

#include <asm/unistd.h>

int s390_pci_mmio_write(unsigned long mmio_addr,

void *user_buffer, size_t length);

int s390_pci_mmio_read(unsigned long mmio_addr,

void *user_buffer, size_t length);

DESCRIPTION

The s390_pci_mmio_write() system call writes length bytes of data from

the user-space buffer user_buffer to the PCI MMIO memory location spec?

ified by mmio_addr. The s390_pci_mmio_read() system call reads length

bytes of data from the PCI MMIO memory location specified by mmio_addr

to the user-space buffer user_buffer.

These system calls must be used instead of the simple assignment or data-transfer operations that are used to access the PCI MMIO memory

areas mapped to user space on the Linux System z platform. The address specified by mmio_addr must belong to a PCI MMIO memory page mapping in the caller's address space, and the data being written or read must not cross a page boundary. The length value cannot be greater than the system page size.

RETURN VALUE

On success, s390_pci_mmio_write() and s390_pci_mmio_read() return 0. On error, -1 is returned and errno is set to one of the error codes listed below.

ERRORS

EFAULT The address in mmio_addr is invalid.

EFAULT user_buffer does not point to a valid location in the caller's

address space.

EINVAL Invalid length argument.

ENODEV PCI support is not enabled.

ENOMEM Insufficient memory.

VERSIONS

These system calls are available since Linux 3.19.

CONFORMING TO

This Linux-specific system call is available only on the s390 architec?

ture. The required PCI support is available beginning with System z

EC12.

NOTES

Glibc does not provide a wrapper for this system call, use syscall(2)

to call it.

SEE ALSO

syscall(2)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man-pages/.

Linux Programmer's Manual 2017-09-15 S390_PCI_MMIO_WRITE(2)