



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'sane-leo.5'

\$ man sane-leo.5

sane-leo(5) SANE Scanner Access Now Easy sane-leo(5)

NAME

sane-leo - SANE backend for LEO Technologies scanners

DESCRIPTION

The sane-leo library implements a SANE (Scanner Access Now Easy) backend that provides access to some LEO SCSI flatbed scanners. This backend should be considered beta-quality software! LEO scanners were also sold under the Across Technologies brand.

The scanners that should work with this backend are:

Vendor	Model	status
--------	-------	--------

Across	FS-1130	tested
--------	---------	--------

LEO	S3	tested
-----	----	--------

The options the backend supports can either be selected through command line options to programs like scanimage(1) or through GUI elements in xsscanimage(1) or xsane(1).

If you have any strange behavior, please report to the backend maintainer or to the SANE mailing list.

Valid command line options and their syntax can be listed by using

```
scainimage --help -d leo
```

Scan Mode

--mode selects the basic mode of operation of the scanner valid choices

are Black & White , Grayscale and Color The Black & White mode

is black and white only (1 bit). Grayscale will produce 256 lev?

els of gray (8 bits). Color will produce a 24 bits color image.

--resolution

selects the resolution for a scan. The scanner can do all reso?

lutions between 1 and 300, in increments of 1.

Geometry options

-l -t -x -y

control the scan area: -l sets the top left x coordinate, -t the top left y coordinate, -x selects the width and -y the height of the scan area. All parameters are specified in millimeters by default.

Enhancement options

--custom-gamma

(grayscale and color mode only) allows the user to specify a gamma table (see the next 3 parameters).

--red-gamma-table

(color mode only) can be used to download a user defined gamma table for the red channel. The table must be 256 bytes long.

--green-gamma-table

(color mode only) can be used to download a user defined gamma table for the green channel. The table must be 256 bytes long.

--blue-gamma-table

(color mode only) can be used to download a user defined gamma table for the blue channel. The table must be 256 bytes long.

--halftone

(Black & White only) select the halftone mask to use. Possible

values are Diamond , 8x8 Coarse Fattening , 8x8 Fine Fattening , 8x8

Bayer and 8x8 Vertical Line

--preview

requests a preview scan. The resolution used for that scan is 28 dpi and the scan area is the maximum allowed. The scan mode is user selected. The default is "no".

CONFIGURATION FILE

The configuration file /etc/sane.d/leo.conf supports only one `informa?` tion: the device name to use (eg /dev/scanner).

FILES

/usr/lib64/sane/libsane-leo.a

The static library implementing this backend.

/usr/lib64/sane/libsane-leo.so

The shared library implementing this backend (present on systems that support dynamic loading).

ENVIRONMENT

`SANE_DEBUG_LEO`

If the library was compiled with debug support enabled, this environment variable controls the debug level for this backend. E.g., a value of 128 requests all debug output to be printed. Smaller levels reduce verbosity.

LIMITATIONS

The windows TWAIN driver has many more options than this SANE backend.

However they are only software adjustments. This backend only implements what the scanner can support.

`SH_BUGS` None known.

SEE ALSO

`sane-scsi(5)`, `scanimate(1)`, `xscanimate(1)`, `xsane(1)`, `sane(7)`

AUTHOR

The package is actively maintained by Frank Zago.

<http://www.zago.net/sane/#leo>