

Full credit is given to the above companies including the OS that this PDF file was generated!

# Rocky Enterprise Linux 9.2 Manual Pages on command 'sane-s9036.5'

### \$ man sane-s9036.5

sane-s9036(5)

SANE Scanner Access Now Easy

sane-s9036(5)

#### NAME

sane-s9036 - SANE backend for Siemens 9036 flatbed scanners

### **DESCRIPTION**

The sane-s9036 library implements a SANE (Scanner Access Now Easy) backend that provides access to Siemens 9036 flatbed scanners.

## **DEVICE NAMES**

This backend expects device names of the form:

special

Where special is the path-name for the special device that corresponds to a SCSI scanner. The special device name must be a generic SCSI de? vice or a symlink to such a device. The program sane-find-scanner(1) helps to find out the correct device. Under Linux, such a device name

could be /dev/sga or /dev/sge, for example. See sane-scsi(5) for de? tails.

### **FILES**

/etc/sane.d/s9036.conf

The backend configuration file (see also description of SANE\_CONFIG\_DIR below).

/usr/lib64/sane/libsane-s9036.a

The static library implementing this backend.

/usr/lib64/sane/libsane-s9036.so

The shared library implementing this backend (present on systems that support dynamic loading).

## **ENVIRONMENT**

## SANE\_CONFIG\_DIR

This environment variable specifies the list of directories that may contain the configuration file. Under UNIX, the directories are separated by a colon (`:'), under OS/2, they are separated by a semi-colon (`;'). If this variable is not set, the config? uration file is searched in two default directories: first, the current working directory (".") and then in /etc/sane.d. If the value of the environment variable ends with the directory sepa? rator character, then the default directories are searched after the explicitly specified directories. For example, setting SANE\_CONFIG\_DIR to "/tmp/config:" would result in directories tmp/config, ., and /etc/sane.d being searched (in this order).

## SANE\_DEBUG\_S9036

If the library was compiled with debug support enabled, this en? vironment variable controls the debug level for this backend.

Higher debug levels increase the verbosity of the output.

Example: export SANE\_DEBUG\_S9036=4

SEE ALSO

sane(7), sane-scsi(5)

**AUTHOR** 

Ingo Schneider

14 Jul 2008 sane-s9036(5)