



Rocky Enterprise Linux 9.2 Manual Pages on command 'sane-umax_pp.5'

\$ man sane-umax_pp.5

sane-umax_pp(5) SANE Scanner Access Now Easy sane-umax_pp(5)

NAME

sane-umax_pp - SANE backend for Umax Astra parallel port flatbed scan?
ners

DESCRIPTION

The sane-umax_pp library implements a SANE (Scanner Access Now Easy) backend that provides access to Umax parallel port flatbed scanners.

The following scanners work with this backend:

Model:

Astra 610P

Astra 1220P

HP3200C

Astra 1600P

Astra 2000P

Genius ColorPage-Life Pro

This backend handles 75x75, 150x150, 300x300, 600x600 and 600x1200 for 1220P/1600P/2000P dpi scan resolutions, and 75x75, 150x150, 300x300 and

300x600 for 610P. In color and gray levels, there is a software linear mode.

The new generation models share a newer version of the 610P ASIC embedded in an EPAT chip. Only parts such as CCD and ADC change from one to another. They even all reports being UMAX Astra 1220P via IEEE1284. There isn't a software method to recognize them properly. Under windows, model is set by the driver installed, regardless of the hardware.

EPP/ECP MODES ONLY

The current version of the backend uses only EPP or ECP mode to communicate with the scanner. PS/2 mode isn't implemented. The 610P only use SPP. It is recommended that you set your parallel port to EPP in BIOS with the current version of this backend. You can leave it to ECP or ECP+EPP, but in this case you may not use ppdev but only direct hardware access if you have to use ECP. ECPEPP will only work if you use a 2.4 or 2.6 kernel with ppdev character device support.

This backend does support parport sharing only if you have a kernel with ppdev support.

Note that if you don't use the ppdev character device, the backend needs to run as root. To allow user access to the scanner run the backend through the network interface (See saned(8) and sane-net(5)). A more relaxed solution (security wise) is to add suid bit to the frontend (See chmod(1)). The backend drop root privileges as soon as it can, right after gaining direct access to IO ports, which lessen risks when being root.

DEVICE NAMES

This backend expects device names of the form:

port value

Where value is :

auto autodetect all parallel ports and probe them for scanner

safe-auto

autodetect all parallel ports and probe them for scanner,

but does not try direct hardware access

/dev/ppi0

uses *BSD ppi device, depending on the number of avail?

able parallel port, you have to use /dev/ppi1, /dev/ppi2,

...

/dev/parport0

uses Linux ppdev device, depending on the number of

available parallel port, you have to use /dev/parport1,

/dev/parport2, ...

0x378 does direct hardware access on the given address. Usual

values are 0x378, 0x278, 0x3BC In this case, you have to

run the scanner as root (*BSD and Linux), or with

'IOPL=yes' on OS/2

NOTE: in all cases, you must have sufficient privileges to get access to the chosen device or address. Depending on the security settings, devices may not be available for all users. You have to change permissions on the /dev/ppi* or /dev/parport* devices.

You can rename any device using the

name devname

model model

vendor vendor

options. These options apply to the last port option.

CONFIGURATION

Please make sure to edit umax_pp.conf before you use the backend.

The contents of the umax_pp.conf file is a list of options and device names that correspond to Umax scanners. Empty lines and lines starting with a hash mark (#) are ignored.

The eight options supported are red-gain, green-gain, blue-gain, red-offset, green-offset, blue-offset, astra, and buffer.

Options red-gain, green-gain and blue-gain allow you to adjust the sensitivity of your scanner for the given color. Values range from 0 (lowest gain) to 15 (highest). If the advanced option "Gain" isn't checked in the frontend, the backend does automatic gain calibration, and do not use user provided values.

Options `red-offset` , `green-offset` and `blue-offset` allow you to adjust the offset of your scanner for the given color. Values range from 0 (lowest offset) to 15 (highest).

Option `astra` allows you to change the model of your scanner. Current auto detection is based on side effects on scanning when using `1220P` command set on other models, so it may fail on unknown hardware combination. Valid values are 610, 1220, 1600 and 2000. It is useful only when autodetection fails to detect properly your scanner model. If your scanner work properly but is reported wrongly, let it be that way. The only valid case to change the model is when your scanner produces "black" or "inverted" scans. In this case you can put the model. Be aware that it will prevent scanner model autodetection.

Option `buffer` allows you to change the size of the scan buffer. The size must be specified in bytes. The default value is 2 megabytes. Decreasing this value will improve the smoothness of progress bar in the frontend, but will stall the scan more often.

FILES

`/etc/sane.d/umax_pp.conf`

The backend configuration file (see also description of `SANE_CONFIG_DIR` below).

`/usr/lib64/sane/libsane-umax_pp.a`

The static library implementing this backend.

`/usr/lib64/sane/libsane-umax_pp.so`

The shared library implementing this backend (present on systems that support dynamic loading).

ENVIRONMENT

`SANE_CONFIG_DIR`

This environment variable specifies the list of directories that may contain the configuration file. Under UNIX, the directories are separated by a colon (':'), under OS/2, they are separated by a semi-colon (';'). If this variable is not set, the configuration file is searched in two default directories: first, the current working directory (".") and then in `/etc/sane.d`. If the

value of the environment variable ends with the directory separator character, then the default directories are searched after the explicitly specified directories. For example, setting `SANE_CONFIG_DIR` to `"/tmp/config:"` would result in directories `tmp/config`, `.`, and `/etc/sane.d` being searched (in this order).

`SANE_DEBUG_UMAX_PP`

If the library was compiled with debug support enabled, this environment variable controls the debug level for this backend. E.g., a value of 128 requests all debug output to be printed. Smaller levels reduce verbosity.

level debug output

- 0 nothing
- 1 errors
- 2 warnings & minor errors
- 3 additional information
- 4 debug information
- 5 code flow (not supported yet)
- 6 special debug information

`SANE_DEBUG_UMAX_PP_LOW`

This variable sets the debug level for the SANE interface for the Umax ASIC. Note that enabling this will spam your terminal with some million lines of debug output.

level debug output

- 0 nothing
- 1 errors
- 8 command blocks
- 16 detailed code flow
- 32 dump datafiles
- 255 everything

SEE ALSO

`sane(7)`, `sane-net(5)`, `saned(8)`

For latest bug fixes and information see

<http://umax1220p.sourceforge.net/>

AUTHOR

Stéphane Voltz <stef.dev@free.fr>

CREDITS

Support for the 610P has been made possible thanks to a hardware donation by William Stuart.

BUG REPORTS

If something doesn't work, please contact me. But I need some information about your scanner to be able to help you...

SANE version

Run `scanimage -V` to determine this
the backend version and your scanner hardware

Run `SANE_DEBUG_UMAX_PP=255 scanimage -L 2>log` as root. If you don't get any output from the `sane-umax_pp` backend, make sure a line `"umax_pp"` is included into your `/etc/sane.d/dll.conf` file.

If your scanner isn't detected, make sure you've defined the right port address, or the correct device in your `umax_pp.conf` file.

the name of your scanner/vendor

also a worthy information. Please also include the optical resolution and lamp type of your scanner, both can be found in the manual of your scanner.

any further comments

if you have comments about the documentation (what could be done better), or you think I should know something, please include it.

14 Jul 2008

sane-umax_pp(5)