



### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'scriptlive.1'***

**\$ man scriptlive.1**

SCRIPTLIVE(1)                      User Commands                      SCRIPTLIVE(1)

#### NAME

scriptlive - re-run session typescripts, using timing information

#### SYNOPSIS

scriptlive [options] [-t] timingfile [-l|-B] typescript

#### DESCRIPTION

This program re-runs a typescript, using stdin typescript and timing information to ensure that input happens in the same rhythm as it originally appeared when the script was recorded.

The session is executed in a newly created pseudoterminal with the user's \$SHELL (or defaults to /bin/bash).

Be careful! Do not forget that the typescript may contains arbitrary commands. It is recommended to use "scriptreplay --stream in --log-in typescript" (or with --log-io instead of --log-in) to verify the typescript before it is executed by scriptlive.

The timing information is what script1 outputs to file specified by --log-timing. The typescript has to contain stdin information and it is what script1 outputs to file specified by --log-in or --log-io.

## OPTIONS

`-I, --log-in file`

File containing script's terminal input.

`-B, --log-io file`

File containing script's terminal output and input.

`-t, --timing file`

File containing script's timing output. This option overrides old-style arguments.

`-T, --log-timing file`

Aliased to `-t`, maintained for compatibility with `script(1)` command-line options.

`-d, --divisor number`

Speed up the replay displaying this number of times. The argument is a floating-point number. It's called divisor because it divides the timings by this factor. This option overrides old-style arguments.

`-m, --maxdelay number`

Set the maximum delay between updates to number of seconds. The argument is a floating-point number. This can be used to avoid long pauses in the typescript replay.

`-V, --version`

Display version information and exit.

`-h, --help`

Display help text and exit.

## EXAMPLES

```
% script --log-timing file.tm --log-in script.in
```

```
Script started, file is script.out
```

```
% date
```

```
<etc, etc>
```

```
% exit
```

```
Script done, file is script.out
```

```
% scriptlive --log-timing file.tm --log-in script.in
```

## AUTHORS

Karel Zak <kzak@redhat.com>

## COPYRIGHT

Copyright ? 2019 Karel Zak

This is free software; see the source for copying conditions. There is

NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

Released under the GNU General Public License version 2 or later.

## SEE ALSO

script(1), scriptreplay(1)

## REPORTING BUGS

For bug reports, use the issue tracker at

<https://github.com/karelzak/util-linux/issues>.

## AVAILABILITY

The scriptlive command is part of the util-linux package which can be downloaded from Linux Kernel Archive

<<https://www.kernel.org/pub/linux/utils/util-linux/>>.

util-linux 2.37.4	2022-02-14	SCRIPTLIVE(1)
-------------------	------------	---------------