



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'sestatus.conf.5'***

### **\$ man sestatus.conf.5**

sestatus.conf(5)      sestatus configuration file      sestatus.conf(5)

#### **NAME**

sestatus.conf - The sestatus(8) configuration file.

#### **DESCRIPTION**

The sestatus.conf file is used by the sestatus(8) command with the -v option to determine what file and process security contexts should be displayed.

The fully qualified path name of the configuration file is:

/etc/sestatus.conf

The file consists of two optional sections as described in the FILE FORMAT section. Whether these exist or not, the following will always be displayed:

The current process context

The init process context

The controlling terminal file context

#### **FILE FORMAT**

The format consists of two optional sections as follows:

[files]

file\_name

[file\_name]

...

[process]

executable\_file\_name

[executable\_file\_name]

...

Where:

[files]

The start of the file list block.

file\_name

One or more fully qualified file names, each on a new line will that will have its context displayed. If the file does not exist, then it is ignored. If the file is a symbolic link, then `sestatus -v` will also display the target file context.

[process]

The start of the process list block.

executable\_file\_name

One or more fully qualified executable file names that should it be an active process, have its context displayed. Each entry is on a new line.

## EXAMPLE

```
# /etc/sestatus.conf
```

```
[files]
```

```
/etc/passwd
```

```
/etc/shadow
```

```
/bin/bash
```

```
/bin/login
```

```
/lib/libc.so.6
```

```
/lib/ld-linux.so.2
```

```
/lib/ld.so.1
```

```
[process]
```

/sbin/mingetty

/sbin/agetty

/usr/sbin/sshd

#### SEE ALSO

selinux(8), sestatus(8)

Security Enhanced Linux

26-Nov-2011

sestatus.conf(5)