



Rocky Enterprise Linux 9.2 Manual Pages on command 'setlogmask.3'

\$ man setlogmask.3

SETLOGMASK(3) Linux Programmer's Manual SETLOGMASK(3)

NAME

setlogmask - set log priority mask

SYNOPSIS

```
#include <syslog.h>

int setlogmask(int mask);
```

DESCRIPTION

A process has a log priority mask that determines which calls to sys?

log(3) may be logged. All other calls will be ignored. Logging is en?

abled for the priorities that have the corresponding bit set in mask.

The initial mask is such that logging is enabled for all priorities.

The setlogmask() function sets this logmask for the calling process, and returns the previous mask. If the mask argument is 0, the current logmask is not modified.

The eight priorities are LOG_EMERG, LOG_ALERT, LOG_CRIT, LOG_ERR, LOG_WARNING, LOG_NOTICE, LOG_INFO, and LOG_DEBUG. The bit correspond?

ing to a priority p is LOG_MASK(p). Some systems also provide a macro

LOG_UPTO(p) for the mask of all priorities in the above list up to and

including p.

RETURN VALUE

This function returns the previous log priority mask.

ERRORS

None.

ATTRIBUTES

For an explanation of the terms used in this section, see at? tributes(7).

??

?Interface ? Attribute ? Value ?

??

?setlogmask() ? Thread safety ? MT-Unsafe race:LogMask ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

LOG_UPTO() will be included in the next release of the POSIX specifica? tion (Issue 8).

SEE ALSO

closelog(3), openlog(3), syslog(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2020-06-09

SETLOGMASK(3)