



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'ssh-pkcs11-helper.8'

\$ man ssh-pkcs11-helper.8

SSH-PKCS11-HELPER(8) BSD System Manager's Manual SSH-PKCS11-HELPER(8)

NAME

ssh-pkcs11-helper ? OpenSSH helper for PKCS#11 support

SYNOPSIS

ssh-pkcs11-helper [-v]

DESCRIPTION

ssh-pkcs11-helper is used by ssh-agent(1) to access keys provided by a PKCS#11 token.

ssh-pkcs11-helper is not intended to be invoked by the user, but from ssh-agent(1).

A single option is supported:

-v Verbose mode. Causes ssh-pkcs11-helper to print debugging mes?

sages about its progress. This is helpful in debugging problems.

Multiple -v options increase the verbosity. The maximum is 3.

Note that ssh-agent(1) will automatically pass the -v flag to
ssh-pkcs11-helper when it has itself been placed in debug mode.

SEE ALSO

[ssh\(1\)](#), [ssh-add\(1\)](#), [ssh-agent\(1\)](#)

HISTORY

ssh-pkcs11-helper first appeared in OpenBSD 4.7.

AUTHORS

Markus Friedl <markus@openbsd.org>

BSD

November 30, 2019

BSD