



Rocky Enterprise Linux 9.2 Manual Pages on command 'strpbrk.3'

\$ man strpbrk.3

STRPBRK(3) Linux Programmer's Manual STRPBRK(3)

NAME

strpbrk - search a string for any of a set of bytes

SYNOPSIS

```
#include <string.h>
```

```
char *strpbrk(const char *s, const char *accept);
```

DESCRIPTION

The `strpbrk()` function locates the first occurrence in the string `s` of any of the bytes in the string `accept`.

RETURN VALUE

The `strpbrk()` function returns a pointer to the byte in `s` that matches one of the bytes in `accept`, or `NULL` if no such byte is found.

ATTRIBUTES

For an explanation of the terms used in this section, see at? tributes(7).

??

?Interface ? Attribute ? Value ?

??

?strpbrk() ? Thread safety ? MT-Safe ?

????????????????????????????????????

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C89, C99, SVr4, 4.3BSD.

SEE ALSO

index(3), memchr(3), rindex(3), strchr(3), string(3), strsep(3), str?
spn(3), strstr(3), strtok(3), wcsprbrk(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A
description of the project, information about reporting bugs, and the
latest version of this page, can be found at
<https://www.kernel.org/doc/man-pages/>.

2015-08-08

STRPBRK(3)