



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'system-auth.5'

```
$ man system-auth.5
```

SYSTEM-AUTH(5)

Linux-PAM Manual

SYSTEM-AUTH(5)

NAME

system-auth - Common configuration file for PAMified services

SYNOPSIS

```
/etc/pam.d/system-auth /etc/pam.d/password-auth /etc/pam.d/fingerprint-  
auth /etc/pam.d/smartcard-auth
```

DESCRIPTION

The purpose of these configuration files are to provide a common interface for all applications and service daemons calling into the PAM library.

The system-auth configuration file is included from nearly all individual service configuration files with the help of the substack directive.

The password-auth fingerprint-auth smartcard-auth configuration files are for applications which handle authentication from different types of devices via simultaneously running individual conversations instead of one aggregate conversation.

NOTES

Previously these common configuration files were included with the help of the include directive. This limited the use of the different action types of modules. With the use of substack directive to include these common configuration files this limitation no longer applies.

BUGS

None known.

SEE ALSO

pam(8), config-util(5), postlogin(5)

The three Linux-PAM Guides, for system administrators, module developers, and application developers.

Red Hat

2010 Dec 22

SYSTEM-AUTH(5)