



Rocky Enterprise Linux 9.2 Manual Pages on command 'systemd-hibernate-resume.8'

\$ man systemd-hibernate-resume.8

SYSTEMD-HIBERNATE-RESUMsystemd-hibernate-rSYSTEMD-HIBERNATE-RESUME@.SERVICE(8)

NAME

systemd-hibernate-resume@.service, systemd-hibernate-resume - Resume
from hibernation

SYNOPSIS

systemd-hibernate-resume@.service

/usr/lib/systemd/systemd-hibernate-resume

DESCRIPTION

systemd-hibernate-resume@.service initiates the resume from
hibernation. It is instantiated with the device to resume from as the
template argument.

systemd-hibernate-resume only supports the in-kernel hibernation
implementation, see Swap suspend[1]. Internally, it works by writing

the major:minor of specified device node to /sys/power/resume.

Failing to initiate a resume is not an error condition. It may mean that there was no resume image (e. g. if the system has been simply powered off and not hibernated). In such case, the boot is ordinarily continued.

SEE ALSO

systemd(1), systemd-hibernate-resume-generator(8)

NOTES

1. Swap suspend

<https://docs.kernel.org/power/swsusp.html>

systemd 252

SYSTEMD-HIBERNATE-RESUME@.SERVICE(8)