



Rocky Enterprise Linux 9.2 Manual Pages on command 'thread-keyring.7'

\$ man thread-keyring.7

THREAD-KEYRING(7) Linux Programmer's Manual THREAD-KEYRING(7)

NAME

thread-keyring - per-thread keyring

DESCRIPTION

The thread keyring is a keyring used to anchor keys on behalf of a process. It is created only when a thread requests it. The thread keyring has the name (description) _tid.

A special serial number value, KEY_SPEC_THREAD_KEYRING, is defined that can be used in lieu of the actual serial number of the calling thread's thread keyring.

From the keyctl(1) utility, '@t' can be used instead of a numeric key ID in much the same way, but as keyctl(1) is a program run after fork(2), this is of no utility.

Thread keyrings are not inherited across clone(2) and fork(2) and are cleared by execve(2). A thread keyring is destroyed when the thread that refers to it terminates.

Initially, a thread does not have a thread keyring. If a thread doesn't have a thread keyring when it is accessed, then it will be created.

ated if it is to be modified; otherwise the operation fails with the error ENOKEY.

SEE ALSO

keyctl(1), keyctl(3), keyrings(7), persistent-keyring(7),
process-keyring(7), session-keyring(7), user-keyring(7),
user-session-keyring(7)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at
<https://www.kernel.org/doc/man-pages/>.

Linux

2020-08-13

THREAD-KEYRING(7)