



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'unimplemented.2'***

### ***\$ man unimplemented.2***

UNIMPLEMENTED(2)      Linux Programmer's Manual      UNIMPLEMENTED(2)

#### NAME

afs\_syscall, break, fattach, fdetach, ftime, getmsg, getpmsg, gtty,  
isastream, lock, madvise1, mpx, prof, profil, putmsg, putpmsg, secu?  
rity, stty, tuxcall, ulimit, vserver - unimplemented system calls

#### SYNOPSIS

Unimplemented system calls.

#### DESCRIPTION

These system calls are not implemented in the Linux kernel.

#### RETURN VALUE

These system calls always return -1 and set errno to ENOSYS.

#### NOTES

Note that ftime(3), profil(3), and ulimit(3) are implemented as library functions.

Some system calls, like alloc\_hugepages(2), free\_hugepages(2), iop?  
erm(2), iopl(2), and vm86(2) exist only on certain architectures.

Some system calls, like ipc(2), create\_module(2), init\_module(2), and  
delete\_module(2) exist only when the Linux kernel was built with sup?

port for them.

#### SEE ALSO

syscalls(2)

#### COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux                      2017-09-15                      UNIMPLEMENTED(2)