

Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'units.7'

\$ man units.7

UNITS(7) Linux Programmer's Manual

UNITS(7)

NAME

units - decimal and binary prefixes

DESCRIPTION

Decimal prefixes

The SI system of units uses prefixes that indicate powers of ten. A

kilometer is 1000 meter, and a megawatt is 1000000 watt. Below the

standard prefixes.

Prefix Name Value

- a atto 10^-18 = 0.000000000000000000
- p pico 10^-12 = 0.00000000001
- n nano 10^-9 = 0.000000001
- ? micro 10^-6 = 0.000001
- m milli 10^-3 = 0.001
- c centi 10^-2 = 0.01

deci 10^-1 = 0.1 d deka 10^1 = 10 da hecto $10^{2} = 100$ h kilo 10^3 = 1000 k mega 10^6 = 1000000 Μ G giga 10^ 9 = 100000000 Т tera 10^12 = 100000000000 Ρ peta 10^15 = 1000000000000000 Е exa 10^18 = 1000000000000000000 Ζ zetta 10^21 = 100000000000000000000

The symbol for micro is the Greek letter mu, often written u in an

ASCII context where this Greek letter is not available. See also

?http://physics.nist.gov/cuu/Units/prefixes.html?

Binary prefixes

The binary prefixes resemble the decimal ones, but have an additional

'i' (and "Ki" starts with a capital 'K'). The names are formed by tak?

ing the first syllable of the names of the decimal prefix with roughly

the same size, followed by "bi" for "binary".

Prefix Name Value

Ki kibi 2^10 = 1024	ŀ
---------------------	---

- Mi mebi 2^20 = 1048576
- Gi gibi 2^30 = 1073741824
- Ti tebi 2^40 = 1099511627776
- Pi pebi 2^50 = 1125899906842624
- Ei exbi 2^60 = 1152921504606846976

See also

?http://physics.nist.gov/cuu/Units/binary.html?

Discussion

Before these binary prefixes were introduced, it was fairly common to

use k=1000 and K=1024, just like b=bit, B=byte. Unfortunately, the $\,M$

is capital already, and cannot be capitalized to indicate binary-ness.

At first that didn't matter too much, since memory modules and disks

came in sizes that were powers of two, so everyone knew that in such contexts "kilobyte" and "megabyte" meant 1024 and 1048576 bytes, re? spectively. What originally was a sloppy use of the prefixes "kilo" and "mega" started to become regarded as the "real true meaning" when computers were involved. But then disk technology changed, and disk sizes became arbitrary numbers. After a period of uncertainty all disk manufacturers settled on the standard, namely k=1000, M=1000 k, G=1000 M.

The situation was messy: in the 14k4 modems, k=1000; in the 1.44 MB diskettes, M=1024000; and so on. In 1998 the IEC approved the standard that defines the binary prefixes given above, enabling people to be precise and unambiguous.

Thus, today, MB = 1000000 B and MiB = 1048576 B.

In the free software world programs are slowly being changed to con?

form. When the Linux kernel boots and says

hda: 120064896 sectors (61473 MB) w/2048KiB Cache

the MB are megabytes and the KiB are kibibytes.

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man-pages/.

Linux 2020-08-13 UNITS(7)