

**NAME**

`GitLab::API::v4::Config` – Load configuration from a file, environment, and/or CLI options.

**SYNOPSIS**

```
use GitLab::API::v4;
use GitLab::API::v4::Config;

my $config = GitLab::API::v4::Config->new();
my $api = GitLab::API::v4->new( $config->args() );
```

**DESCRIPTION**

This module is used by `gitlab-api-v4` to load configuration.

If you are using `GitLab::API::v4` directly then this module will not be automatically used, but you are welcome to explicitly use it as shown in the “SYNOPSIS”.

**ARGUMENTS****file**

The file to load configuration from. The file should hold valid JSON.

By default this will be set to `.gitlab-api-v4-config` in the current user’s home directory.

This can be overridden with the `GITLAB_API_V4_CONFIG_FILE` environment variable or the `--config-file=...` command line argument.

**ATTRIBUTES****opt\_args**

Returns a hashref of arguments derived from command line options.

Supported options are:

```
--config_file=...
--url=...
--private-token=...
--access-token=...
--retries=...
```

Note that the options are read from, and removed from, `@ARGV`. Due to this the arguments are saved internally and re-used for all instances of this class so that there are no weird race conditions.

**env\_args**

Returns a hashref of arguments derived from environment variables.

Supported environment variables are:

```
GITLAB_API_V4_CONFIG_FILE
GITLAB_API_V4_URL
GITLAB_API_V4_PRIVATE_TOKEN
GITLAB_API_V4_ACCESS_TOKEN
GITLAB_API_V4_RETRIES
```

**file\_args**

Returns a hashref of arguments gotten by decoding the JSON in the “file”.

**args**

Returns a final, combined, hashref of arguments containing everything in “`opt_args`”, “`env_args`”, and “`file_args`”. If there are any duplicate arguments then “`opt_args`” has highest precedence, “`env_args`” is next, and at the bottom is “`file_args`”.

**METHODS****get\_options****configure**

When called this method interactively prompts the user for argument values and then encodes them as JSON and stores them in “`file`”. The file will be `chmod’ed` 0600 so that only the current user may read or write

to the file.

**SUPPORT**

See “SUPPORT” in GitLab::API::v4.

**AUTHORS**

See “AUTHORS” in GitLab::API::v4.

**COPYRIGHT AND LICENSE**

See “COPYRIGHT AND LICENSE” in GitLab::API::v4.