

## NAME

Parse::DebianChangelog::Entry – represents one entry in a Debian changelog

## SYNOPSIS

## DESCRIPTION

### Methods

*init*

Creates a new object, no options.

*new*

Alias for *init*.

*is\_empty*

Checks if the object is actually initialized with data. Due to limitations in Parse::DebianChangelog this currently simply checks if one of the fields Source, Version, Maintainer, Date, or Changes is initialized.

### Accessors

The following fields are available via accessor functions (all fields are string values unless otherwise noted):

- Source
- Version
- Distribution
- Urgency
- ExtraFields (all fields except for urgency as hash)
- Header (the whole header in verbatim form)
- Changes (the actual content of the bug report, in verbatim form)
- Trailer (the whole trailer in verbatim form)
- Closes (Array of bug numbers)
- Maintainer (name **and** email address)
- Date
- Timestamp (Date expressed in seconds since the epoche)
- ERROR (last parse error related to this entry in the format described at Parse::DebianChangelog::get\_parse\_errors.

## SEE ALSO

Parse::DebianChangelog

## AUTHOR

Frank Lichtenheld, <frank@lichtenheld.de>

## COPYRIGHT AND LICENSE

Copyright (C) 2005 by Frank Lichtenheld

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110–1301 USA