



Linux Ubuntu 26.04 Manual Pages on command 'XtGetSelectionParameters.3'

\$ man XtGetSelectionParameters.3

XtGetSelectionParameters(3) XT FUNCTIONS XtGetSelectionParameters(3)

NAME

XtGetSelectionParameters - retrieve target parameters for a selection request with a single target

SYNTAX

```
#include <X11/Intrinsic.h>
```

```
void XtGetSelectionParameters(Widget owner, Atom selection, XtRequestId request_id, Atom
    *type_return, XtPointer *value_return, unsigned long *length_return, int *format_re?
    turn);
```

ARGUMENTS

owner Specifies the widget that owns the specified selection.

selection Specifies the selection being processed.

request_id

Specifies the requestor id in the case of incremental selections, or NULL in the case of atomic transfers.

type_return

Specifies a pointer to an atom in which the property type of the parameters will be stored.

value_return

Specifies a pointer into which a pointer to the parameters are to be stored. A NULL will be stored if no parameters accompany the request.

length_return

Specifies a pointer into which the number of data elements in value_return of size indicated by format_return will be stored.

format_return

Specifies a pointer into which the size in bits of the parameter data in the elements of value_return will be stored.

DESCRIPTION

XtGetSelectionParameters may only be called from within an XtConvertSelectionProc or from within the last call to an XtConvertSelectionIncrProc with a new request_id.

SEE ALSO

XtSetSelectionParameters(3)

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface

X Version 11

libXt 1.2.1

XtGetSelectionParameters(3)