



Linux Ubuntu 26.04 Manual Pages on command 'XtGetSelectionRequest.3'

\$ man XtGetSelectionRequest.3

XtGetSelectionRequest(3) XT FUNCTIONS XtGetSelectionRequest(3)

NAME

XtGetSelectionRequest - retrieve the event that triggered the XtConvertSelectionProc

SYNTAX

```
#include <X11/Intrinsic.h>
```

```
XSelectionRequestEvent* XtGetSelectionRequest(Widget w, Atom selection, XtRequestId re?  
quest_id);
```

ARGUMENTS

w Specifies the widget.

selection Specifies the selection being processed.

request_id

Specifies the requestor id in the case of incremental selections, or NULL in the case of atomic transfers.

DESCRIPTION

XtGetSelectionRequest may only be called from within an XtConvertSelectionProc procedure and returns a pointer to the SelectionRequest event that caused the conversion procedure to be

invoked. Request_id specifies a unique id for the individual request in the case that multiple incremental transfers are outstanding. For atomic transfers, request_id must be specified as NULL. If no SelectionRequest event is being processed for the specified widget, selection, and request_id, XtGetSelectionRequest returns NULL.

SEE ALSO

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface

X Version 11

libXt 1.2.1

XtGetSelectionRequest(3)