



Linux Ubuntu 26.04 Manual Pages on command 'XtKeysymToKeycodeList.3'

\$ man XtKeysymToKeycodeList.3

XtGetKeysymTable(3) XT FUNCTIONS XtGetKeysymTable(3)

NAME

XtGetKeysymTable, XtKeysymToKeycodeList - query keysyms and keycodes

SYNTAX

```
#include <X11/Intrinsic.h>
```

```
KeySym*    XtGetKeysymTable(Display*    display,    KeyCode*    min_keycode_return,    int  
          *keysyms_per_keycode_return);
```

```
void XtKeysymToKeycodeList(Display* display, KeySym keysym, KeyCode** keycodes_return, Car?  
          dinal* keycount_return);
```

ARGUMENTS

display Specifies the display whose table is required.

min_keycode_return

Returns the minimum KeyCode valid for the display.

keysyms_per_keycode_return

Returns the number of KeySyms stored for each KeyCode.

keysym Specifies the KeySym for which to search.

keycodes_return

Returns a list of KeyCodes that have keysym associated with them, or NULL if key?

count_return is 0.

keycount_return

Returns the number of KeyCodes in the keycode list.

DESCRIPTION

XtGetKeysymTable returns a pointer to the Intrinsics' copy of the server's KeyCode-to-Keysym table. This table must not be modified.

The XtKeysymToKeycodeList procedure returns all the KeyCodes that have keysym in their entry for the keyboard mapping table associated with display. The caller should free the storage pointed to by keycodes_return using XtFree when it is no longer useful.

SEE ALSO

X Toolkit Intrinsics - C Language Interface

Xlib - C Language X Interface

X Version 11

libXt 1.2.1

XtGetKeysymTable(3)