



## ***Linux Ubuntu 26.04 Manual Pages on command 'XtSetMappedWhenManaged.3'***

***\$ man XtSetMappedWhenManaged.3***

XtMapWidget(3)

XT FUNCTIONS

XtMapWidget(3)

### NAME

XtMapWidget, XtSetMappedWhenManaged, XtUnmapWidget - map and unmap widgets

### SYNTAX

```
#include <X11/Intrinsic.h>
```

```
void XtMapWidget(Widget w);
```

```
void XtSetMappedWhenManaged(Widget w, Boolean map_when_managed);
```

```
void XtUnmapWidget(Widget w);
```

### ARGUMENTS

map\_when\_managed

Specifies a Boolean value that indicates the new value of the map\_when\_managed field.

w Specifies the widget.

### DESCRIPTION

If the widget is realized and managed and if the new value of map\_when\_managed is True, XtSetMappedWhenManaged maps the window. If the widget is realized and managed and if the new value of map\_when\_managed is False, it unmaps the window. XtSetMappedWhenManaged is a convenience function that is equivalent to (but slightly faster than) calling XtSetValues and setting the new value for the mappedWhenManaged resource. As an alternative to using XtSetMappedWhenManaged to control mapping, a client may set mapped\_when\_managed to False and use XtMapWidget and XtUnmapWidget explicitly.

### SEE ALSO

XtManageChildren(3)

X Toolkit Intrinsics - C Language Interface

Xlib - C Language X Interface

X Version 11

libXt 1.2.1

XtMapWidget(3)