



Linux Ubuntu 26.04 Manual Pages on command 'XtVaCreateArgsList.3'

\$ man XtVaCreateArgsList.3

XtVaCreateArgsList(3)	XT FUNCTIONS	XtVaCreateArgsList(3)
-----------------------	--------------	-----------------------

NAME

XtVaCreateArgsList - dynamically allocate a varargs list

SYNTAX

```
#include <X11/Intrinsic.h>
```

```
XtVarArgsList XtVaCreateArgsList(XtPointer unused, ...);
```

ARGUMENTS

unused Must be specified as NULL.

... Specifies a variable parameter list of resource name and value pairs.

DESCRIPTION

The XtVaCreateArgsList function allocates memory and copies its arguments into a single list pointer, which may be used with XtVaNestedList. The end of both lists is identified by a name entry containing NULL. Any entries of type XtVaTypedArg are copied as specified without applying conversions. Data passed by reference (including Strings) are not copied, only the pointers themselves; the caller must ensure that the data remain valid for the lifetime of the created varargs list. The list should be freed using XtFree when no longer needed.

SEE ALSO

[X Toolkit Intrinsics - C Language Interface](#)

[Xlib - C Language X Interface](#)

[X Version 11](#)

[libXt 1.2.1](#)

[XtVaCreateArgsList\(3\)](#)