



Full credit is given to the above companies including the OS that this PDF file was generated!

Linux Ubuntu 26.04 Manual Pages on command '_sysctl.2'

\$ man _sysctl.2

sysctl(2) System Calls Manual sysctl(2)

NAME

sysctl - read/write system parameters

SYNOPSIS

```
#include <unistd.h>
```

```
#include <linux/sysctl.h>
```

```
[[deprecated]] int _sysctl(struct __sysctl_args *args);
```

DESCRIPTION

This system call no longer exists on current kernels! See NOTES.

The `_sysctl()` call reads and/or writes kernel parameters. For example, the hostname, or the maximum number of open files. The argument has the form

```
struct __sysctl_args {
    int  *name; /* integer vector describing variable */
    int  nlen; /* number of elements of this vector */
    void *oldval; /* 0 or address where to store old value */
    size_t *oldlenp; /* available room for old value,
                     overwritten by actual size of old value */
    void *newval; /* 0 or address of new value */
    size_t newlen; /* size of new value */
};
```

This call does a search in a tree structure, possibly resembling a directory tree under `/proc/sys`, and if the requested item is found calls some appropriate routine to read or modify the value.

RETURN VALUE

Upon successful completion, `_sysctl()` returns 0. Otherwise, a value of -1 is returned and `errno` is set to indicate the error.

ERRORS

`EACCES`

`EPERM` No search permission for one of the encountered "directories", or no read permission where `oldval` was nonzero, or no write permission where `newval` was nonzero.

`EFAULT` The invocation asked for the previous value by setting `oldval` non-NULL, but allowed zero room in `oldlenp`.

`ENOTDIR`

name was not found.

STANDARDS

Linux.

HISTORY

4.4BSD, Linux 1.3.57. Removed in Linux 5.5, glibc 2.32.

Only Linux has the `/proc/sys` mirror, and the object naming schemes differ between Linux and 4.4BSD, but the declaration of the `sysctl()` function is the same in both.

NOTES

Use of this system call was long discouraged: since Linux 2.6.24, uses of this system call result in warnings in the kernel log, and in Linux 5.5, the system call was finally removed.

Use the `/proc/sys` interface instead.

Note that on older kernels where this system call still exists, it is available only if the kernel was configured with the `CONFIG_SYSCTL_SYSCALL` option. Furthermore, glibc does not provide a wrapper for this system call, necessitating the use of `syscall(2)`.

BUGS

The object names vary between kernel versions, making this system call worthless for applications.

Not all available objects are properly documented.

It is not yet possible to change operating system by writing to `/proc/sys/kernel/ostype`.

EXAMPLES

```
#define _GNU_SOURCE
#include <stdcountof.h>
#include <stdio.h>
```

```

#include <stdlib.h>

#include <string.h>

#include <sys/syscall.h>

#include <unistd.h>

#include <linux/sysctl.h>

int __sysctl(struct __sysctl_args *args);

#define OSNAMESZ 100

int
main(void)
{
    int          name[] = { CTL_KERN, KERN_OSTYPE };
    char         osname[OSNAMESZ];
    size_t       osnamelth;
    struct __sysctl_args args;
    memset(&args, 0, sizeof(args));
    args.name = name;
    args.nlen = countof(name);
    args.oldval = osname;
    args.oldlenp = &osnamelth;
    osnamelth = sizeof(osname);
    if (syscall(SYS__sysctl, &args) == -1) {
        perror("__sysctl");
        exit(EXIT_FAILURE);
    }
    printf("This machine is running %*s\n", (int) osnamelth, osname);
    exit(EXIT_SUCCESS);
}

```

SEE ALSO

proc(5)

Linux man-pages 6.17

2026-02-10

sysctl(2)