



Linux Ubuntu 26.04 Manual Pages on command 'acorn.1'

\$ man acorn.1

acorn(1) acorn(1)

NAME

acorn - parse JavaScript file

SYNOPSIS

```
acorn [--ecma3 | --ecma5 | --ecma6 | --ecma7 | ... | --ecma2015 | --ecma2016] [--tokenize]
      [--locations] [--allow-hash-bang] [--compact] [--silent] [--module] [--help] [--]
      [infile]
```

DESCRIPTION

acorn is a utility to parse a JavaScript file from the command line. It accepts as arguments the input file. The utility spits out the syntax tree as JSON data.

OPTIONS

--ecma3, --ecma5, --ecma6, --ecma7, ..., --ecma2015, --ecma2016

Sets the ECMAScript version to parse. Default is version 7.

--tokenize

Tokenizer mode of the parser.

--locations

Attaches a "loc" object to each node with "start" and "end" subobjects, each of which contains the one-based line and zero-based column numbers in {line, column} form.

--allow-hash-bang

If enabled, skip the leading hashbang line.

--compact

No whitespace is used in the AST output.

--silent

Do not output the AST, just return the exit status.

--module

Indicates the code shouldn't be parsed as a script but as a module. This influences global strict mode and 'import' and 'export' declarations.

--help Print the usage information and quit.

1772284640

acorn(1)